

INDUSTRIAL COMPONENT DATA

M22-DH-R-X0 216655 Y7-216655 EATON ELECTRIC

Pushbutton, raised, red 0, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DH-R-X0



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DH-R-X0
Catalog number	Y7-216655
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-26D8B7E1D6
Generated	2026-08-02

Product Overview

Pushbutton, raised, red 0, momentary

M22-DH-R-X0

Pushbutton, RMQ-Titan, Extended, momentary, red, inscribed, Bezel: titanium

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Extended, momentary, button plate: red, Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

Pushbutton, RMQ-Titan, Extended, momentary, red, inscribed, Bezel: titaniumPushbutton, Product range: RMQ-Titan, Single unit, Design: Extended, momentary, button plate: red, Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

General specificationsProduct nameEaton Moeller® series M22 PushbuttonPart

no.M22-DH-R-X0EAN4015082166557Product Length/Depth30 millimetreProduct height35 millimetreProduct width30

millimetreProduct weight0.012 kilogramCompliancesCE MarkedCertificationsCSA Std. C22.2 No. 94-91

IEC 60947-5

UL 508

CSA Std. C22.2 No. 14-05

EN 60947-5

VDE

IEC/EN 60947-5

CSA-C22.2 No. 14-05

UL

CE

CSA File No.: 012528

VDE 0660

CSA

UL Category Control No.: NKCR

CSA-C22.2 No. 94-91

CSA Class No.: 3211-03

IEC/EN 60947

UL File No.: E29184

GL

LR

DNVProduct TradenameM22Product TypePushbuttonProduct Sub TypeNoneFeatures & FunctionsBezel

colorTitaniumBezel materialPlasticDesignExtended

ClassicalFeaturesLabelledFitted with:Front ringInscriptionOGeneral informationDegree of protectionNEMA 4X

NEMA 3R

NEMA 12

NEMA 13

IP67

IP69K

IP66Degree of protection (front side)IP67/IP69K

NEMA 4XLifespan, mechanical5,000,000 OperationsOpening diameter22.5 mmOperating frequency3600

Operations/hProduct categoryRMQ-TitanSizeFront dimensions: 22 x 22 mmTypePushbutton actuatorAmbient conditions,
mechanicalMounting positionAs requiredShock resistanceMechanical...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DH-R-X0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.