

## INDUSTRIAL COMPONENT DATA

# M22-DRH-R 216667 Y7-216667 EATON ELECTRIC Pushbutton, raised, red, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DRH-R



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | M22-DRH-R                     |
| Catalog number  | Y7-216667                     |
| Category        | Front element for push button |
| Minimum order   | 5 Pcs                         |
| Document ID     | EO-6641CBACED                 |
| Generated       | 2026-08-04                    |

## Product Overview

Pushbutton, raised, red, maintained

M22-DRH-R

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Extended, maintained, red, Blank, Bezel: titanium

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Extended, maintained, button plate: red, Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Instructions: Stay-put/spring-return function can be changed on device, Standards: IEC/EN 60947, VDE 0660

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216667 Model Code M22-DRH-R EAN 4015082166670 Product Length/Depth 30 mm Product Height 35 mm Product Width 30 mm Product Weight 0.013 kg

Compliances CE Marked Certifications EN 60947-5

CSA Std. C22.2 No. 94-91

UL 508

IEC 60947-5

CSA Std. C22.2 No. 14-05

VDE

CSA-C22.2 No. 94-91

CE

CSA File No.: 012528

IEC/EN 60947-5

CSA Class No.: 3211-03

IEC/EN 60947

UL

UL Category Control No.: NKCR

UL File No.: E29184

CSA-C22.2 No. 14-05

CSA

VDE 0660

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Extended

Classical Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device Inscription Blank

General

Degree of protection NEMA 12

NEMA 13

IP66

NEMA 3R

IP67

IP69K

NEMA 4X Degree of protection (front side) NEMA 4X

IP67/IP69K Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 22.5 mm Operating frequency 1800 Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cons...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DRH-R with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.