

INDUSTRIAL COMPONENT DATA

M22S-DH-R 216642 Y7-216642 EATON ELECTRIC Pushbutton, raised, red, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DH-R



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-DH-R
Catalog number	Y7-216642
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-EDA3B8759F
Generated	2026-08-04

Product Overview

Pushbutton, raised, red, momentary

M22S-DH-R

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Extended, momentary, red, Blank, Bezel: black

Pushbutton, Product range: RMQ-Titan, Single unit, Design: Extended, momentary, button plate: red, Button plate Blank,

Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections,

Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Pushbutton Catalog Number 216642 Model Code M22S-DH-R EAN

4015082166427 Product Length/Depth 30 mm Product Height 35 mm Product Width 30 mm Product Weight 0.012 kg

Certifications IEC/EN 60947-5

UL Category Control No.: NKCR

VDE 0660

CSA

CSA-C22.2 No. 94-91

CSA File No.: 012528

IEC/EN 60947

UL
CE
CSA Class No.: 3211-03
UL File No.: E29184
CSA-C22.2 No. 14-05
UL 508
DNV
GL
LR Features & Functions
Bezel color Black Bezel material Plastic Design Extended
Classical Fitted with: Front ring Inscription Blank General
Degree of protection IP69K
IP67
NEMA 4X
NEMA 12
NEMA 3R
IP66
NEMA 13 Degree of protection (front side) IP67/IP69K
NEMA 4X Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h
Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Pushbutton actuator Ambient conditions, mechanical
Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Communication
Connection to SmartWire-DT With SWD-RMQ connections
Yes Actuator
Actuating force 5 N Actuator color Red Actu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DH-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.