


INDUSTRIAL COMPONENT DATA

Q25DR-WS 088701 Y7-88701 EATON ELECTRIC Pushbutton, white, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: Q25DR-WS



Manufacturer	EATON - MOELLER
MPN / Reference	Q25DR-WS
Catalog number	Y7-88701
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-FF951EA0BA
Generated	2026-08-02

Product Overview

Pushbutton, white, maintained

Flush push button 16 mm Interlocking White

Eaton Moeller® series RMQ16 Pushbutton, white, maintained Q25DR-WS

Pushbutton, Product range: RMQ16, Single unit, Design: Flat, maintained, button plate: White, Button plate Blank, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: 25 x 25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Pushbutton Catalog Number 088701 Model Code Q25DR-WS EAN 4015080887010 Product Length/Depth 50 mm Product Height 25 mm Product Width 25 mm Product Weight 0.008 kg

Certifications UL 508

CE

IEC/EN 60947-5

UL File No.: E29184

UL Category Control No.: NKCR

UL

CSA

VDE 0660

CSA-C22.2 No. 14-05

IEC/EN 60947

CSA File No.: 46552

CSA Class No.: 3211-03 Features & Functions

Bezel color Black Bezel material Plastic Design Flat Fitted with: Front ring Inscription Blank General

Degree of protection IP65

NEMA 1 Degree of protection (front side) IP65

NEMA 1 Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 1800 Operations/h

Product category RMQ16 Size Front dimensions: 25 x 25 mm Terminal capacity 0.5 - 1.0 mm² Terminal size 2.8 x 0.8 mm to DIN 46244, Blade terminal

2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors Type Pushbutton actuator Ambient conditions, mechanical Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Actuator

Actuating force 4 N Actuator col...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25DR-WS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.