

## INDUSTRIAL COMPONENT DATA

# Z-PUL230/SS 276297 Y7-276297 EATON ELECTRIC

## Pushbutton with LED, 230AC/DC, 2N/O, 16A, orange, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-PUL230/SS



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | Z-PUL230/SS                        |
| Catalog number  | Y7-276297                          |
| Category        | Push button for distribution board |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-7B0F955CEF                      |
| Generated       | 2026-08-06                         |

### Product Overview

Pushbutton with LED, 230AC/DC, 2N/O, 16A, orange, 1HP

Z-PUL230/SS

Eaton Distribution parts. Pushbutton with LED, 230AC/DC, 2N/O, 16A, orange, 1HP

Pushbutton with LED, function: 2 N/O, rated operational current 16A, rated operating voltage of the switch 250 V AC, rated operating voltage of LED 230V AC/DC, color of pushbutton green, color of the LED orange, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 1-10 mm<sup>2</sup>, type conform to IEC/EN 60669, VDE 0632

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

### Additional Product Information

#### General specifications

Product Name Eaton Distribution parts Catalog Number 276297 Model Code Z-PUL230/SS EAN 4015082762971 Product Length/Depth 80 mm Product Height 70 mm Product Width 17.5 mm Product Weight 0.08 kg Compliances RoHS conform Certifications CE Product specifications

Actuator color Green Fitted with: Signal lamp Used with Enclosure 1000 x 600 mm Equipment heat dissipation, current-dependent 4 W Color calotte Other Lamp socket Other Built-in depth 60 mm Heat dissipation per pole, current-dependent 2 W Lamp power 2 W Lamp voltage - max 240 V Lamp voltage - min 110 V Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 2 Voltage type AC Lamp type LED Degree of protection IP40 Rated operational current for specified heat dissipation (In) 16 A

Switching current 16 A Switching voltage 250 V Width in number of modular spacings 1

ETIM for 276297 Modular devices for distribution board/surface mounting (EC001546)

Feature Name

Feature Value

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as normally open contact (EF008256)

2

Number of contacts as change-over contact (EF008257)

0

Switching current (EF000188)

16 A

Switching voltage (EF003586)

250 V

Voltage type (EF000187)

AC

With signal lamp (EF000198)

Yes

Colour calotte (EF004668)

Other

Lamp type (EF002423)

LED

Lamp socket (EF004870)

Other

Max. lamp power (EF000260)

2 W

Lamp voltage (EF008856)

110 V

Colour butt...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-PUL230/SS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.