

INDUSTRIAL COMPONENT DATA

Z-PUL24/SO 276296 Y7-276296 EATON ELECTRIC Pushbutton with LED, 24AC/DC, 1N/O+1N/C, 16A, orange, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-PUL24/SO



Manufacturer	EATON - MOELLER
MPN / Reference	Z-PUL24/SO
Catalog number	Y7-276296
Category	Push button for distribution board
Minimum order	1 Pcs
Document ID	EO-6B5AB4294F
Generated	2026-08-05

Product Overview

Pushbutton with LED, 24AC/DC, 1N/O+1N/C, 16A, orange, 1HP

Z-PUL24/SO

Pushbutton with LED, function: 1 N/O and 1 N/C, rated operational current 16A, rated operating voltage of the switch 250 V AC, rated operating voltage of LED 24V AC/DC, color of pushbutton black, color of the LED orange, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 1-10 mm², type conform to IEC/EN 60669, VDE 0632

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Pushbutton with LED, 24AC/DC, 1N/O+1N/C, 16A, orange, 1HP
Pushbutton with LED, function: 1 N/O and 1 N/C, rated operational current 16A, rated operating voltage of the switch 250 V AC, rated operating voltage of LED 24V AC/DC, color of pushbutton black, color of the LED orange, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 1-10 mm², type conform to IEC/EN 60669, VDE 0632

General specifications
Product name Eaton Distribution parts
Part no. Z-PUL24/SO
EAN 4015082762964
Product

Length/Depth 80 millimetre
Product height 70 millimetre
Product width 17.5 millimetre
Product weight 0.08

kilogram
Compliance RoHS conform
Product Tradename None
Product Type Distribution parts
Product Sub Type None
Public

Consumption Yes
Product Family Description ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable Yes
Product

Specification Details
Actuator color Black
Built-in depth 60 mm
Color calotte Other
Degree of protection IP40
Equipment heat dissipation, current-dependent 4 W
Fitted with: Signal lamp
Heat dissipation per pole, current-dependent 2 W
Lamp power 2

WLamp socketOtherLamp typeLEDLamp voltage - max24 VLamp voltage - min12 VNumber of contacts (change-over contacts)0Number of contacts (normally closed contacts)1Number of contacts (normally open contacts)1Rated operational current for specified heat dissipation (In)16 ASwitching current16 ASwitching voltage250 VVoltage typeACWidth in number of modular spacings1Technical data ETIM 9.0
Devices for distribution board-/...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-PUL24/SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.