

INDUSTRIAL COMPONENT DATA

Q25DR-X 093626 Y7-93626 EATON ELECTRIC Pushbutton, without button plate, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: Q25DR-X



Manufacturer	EATON - MOELLER
MPN / Reference	Q25DR-X
Catalog number	Y7-93626
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-4E7B4EADD5
Generated	2026-08-03

Product Overview

Pushbutton, without button plate, maintained

Flush push button 16 mm Interlocking without button plate

Eaton Moeller® series RMQ16 Pushbutton, without button plate, maintained Q25DR-X

Pushbutton, Product range: RMQ16, Single unit, Design: Flat, maintained, button plate: Without button plate, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: 25 x 25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Pushbutton Catalog Number 093626 Model Code Q25DR-X EAN

4015080936268 Product Length/Depth 50 mm Product Height 25 mm Product Width 25 mm Product Weight 0.008 kg

Certifications UL 508

CSA-C22.2 No. 14-05

IEC/EN 60947-5

VDE 0660

UL Category Control No.: NKCR

CSA File No.: 46552

CSA Class No.: 3211-03

IEC/EN 60947

UL
CSA
UL File No.: E29184
CE Features & Functions
Bezel color Black Bezel material Plastic Design Flat Fitted with: Front ring General
Degree of protection IP65
NEMA 1 Degree of protection (front side) NEMA 1
IP65 Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 1800 Operations/h Product category RMQ16 Size Front dimensions: 25 x 25 mm Terminal capacity 0.5 - 1.0 mm² Terminal size 2.8 x 0.8 mm to DIN 46244, Blade terminal
2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors Type Pushbutton actuator Ambient conditions, mechanical Mounting position As required Shock resistance 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Actuator
Actuating force 4 N Actuator color Without button....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25DR-X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.