

INDUSTRIAL COMPONENT DATA

Q18D-X 093623 Y7-93623 EATON ELECTRIC Pushbutton, without button plate, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: Q18D-X



Manufacturer	EATON - MOELLER
MPN / Reference	Q18D-X
Catalog number	Y7-93623
Category	Front element for push button
Minimum order	10 Pcs
Document ID	EO-3E9C4DD2A8
Generated	2026-08-03

Product Overview

Pushbutton, without button plate, momentary

Flush pushbutton 16 mm 18x18 mm Return without button plate

Eaton Moeller® series RMQ16 Pushbutton, without button plate, momentary Q18D-X

Pushbutton, Product range: RMQ16, Single unit, Design: Flat, momentary, button plate: Without button plate, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: 18 x 18

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Pushbutton Catalog Number 093623 Model Code Q18D-X EAN

4015080936237 Product Length/Depth 50 mm Product Height 18 mm Product Width 18 mm Product Weight 0.007 kg

Certifications CSA Class No.: 3211-03

CSA File No.: 46552

UL File No.: E29184

VDE 0660

CE

IEC/EN 60947

UL Category Control No.: NKCR

UL

CSA-C22.2 No. 14-05

CSA

UL 508

IEC/EN 60947-5 Features & Functions

Bezel color Black Bezel material Plastic Design Flat Fitted with: Front ring General

Degree of protection NEMA 1

IP65 Degree of protection (front side) IP65

NEMA 1 Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 3600 Operations/h

Product category RMQ16 Size Front dimensions: 18 x 18 mm Type Pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Actuator

Actuating force 4 N Actuator color Without button plate Actuator function Spring-return

Momentary Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-de...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q18D-X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.