

INDUSTRIAL COMPONENT DATA

Q25DR-GE 088404 Y7-88404 EATON ELECTRIC Pushbutton, yellow, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: Q25DR-GE



Manufacturer	EATON - MOELLER
MPN / Reference	Q25DR-GE
Catalog number	Y7-88404
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-AA8E6C7B54
Generated	2026-07-27

Product Overview

Pushbutton, yellow, maintained

Flush Push Button 16 mm Interlocking Yellow

Eaton Moeller® series RMQ16 Pushbutton, yellow, maintained Q25DR-GE

Pushbutton, Product range: RMQ16, Single unit, Design: Flat, maintained, button plate: yellow, Button plate Blank, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: 25 x 25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Pushbutton Catalog Number 088404 Model Code Q25DR-GE EAN 4015080884040 Product Length/Depth 50 mm Product Height 25 mm Product Width 25 mm Product Weight 0.008 kg

Certifications VDE 0660

IEC/EN 60947-5

CSA-C22.2 No. 14-05

UL File No.: E29184

CSA

IEC/EN 60947

CE

CSA File No.: 46552

UL
UL 508
CSA Class No.: 3211-03
UL Category Control No.: NKCR Features & Functions
Bezel color Black Bezel material Plastic Design Flat Fitted with: Front ring Inscription Blank General
Degree of protection IP65
NEMA 1 Degree of protection (front side) IP65
NEMA 1 Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 1800 Operations/h
Product category RMQ16 Size Front dimensions: 25 x 25 mm Terminal capacity 0.5 - 1.0 mm² Terminal size 2.8 x 0.8 mm
to DIN 46244, Blade terminal
2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors Type Pushbutton actuator Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature
(enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Climatic proofing Damp heat, cyclic, to IEC
60068-2-30
Damp heat, constant, to IEC 60068-2-78 Actuator
Actuating force 4 N Actuator col...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25DR-GE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.