

INDUSTRIAL COMPONENT DATA

PV-3A10/1P PV-3A10-1P EATON ELECTRIC Fuse-link, high speed, 10 A, DC 1000 V, IEC 60269-6 type A, 10 x 38 mm,..

Brand: EATON - MOELLER | Manufacturer Part Number: PV-3A10/1P



Manufacturer	EATON - MOELLER
MPN / Reference	PV-3A10/1P
Catalog number	PV-3A10-1P
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-A99956A1A9
Generated	2026-08-06

Product Overview

3AMP 1000V DC SOLAR PCB-1 10 X 38MM

PV-3A10/1P - Fuse-link, high speed, 3 A, DC 1000 V, IEC 60269-6 type A, 10 x 38 mm, gPV, UL PV, IEC, UL, PCB fixing Fuse, Fuse-link, high speed, 3 A, DC 1000 V, IEC 60269-6 type A, 10 x 38 mm, gPV, UL PV, IEC, UL, cylindrical with PCB fixing, protection of solar PV strings, IEC 60269-6, UL 248-19, Breaking Capacity 50 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 3 A, DC 1000 V, IEC 60269-6 type A, 10 x 38 mm, gPV, UL PV, IEC, UL, PCB fixing Fuse, Fuse-link, high speed, 3 A, DC 1000 V, IEC 60269-6 type A, 10 x 38 mm, gPV, UL PV, IEC, UL, cylindrical with PCB fixing, protection of solar PV strings, IEC 60269-6, UL 248-19, Breaking Capacity 50 kA

General specificationsProduct nameEaton Bussmann series photovoltaic fusesPart

no.PV-3A10/1PEAN5027590506137Product Length/Depth40 millimetreProduct height13 millimetreProduct width7

millimetreProduct weight12.1 gramCompliancesRoHS Compliant

CE MarkedCertificationsUL Listed

CSA Certified

IEC Rated

CCCProduct TradenameNoneProduct TypeHigh speed photovoltaic fuseProduct Sub TypeNoneElectrical dataAmperage Rating3 AVoltage rating1000 VdcInterrupt rating50 kAICClassClass gPVProduct specificationsApplicationPhotovoltaic stringsFuse typePV-A10-1PFuse indicatorOtherFuse size10 x 38 mmQuantity10Compatible fuse holdersSuitable forCHPV

Modular fuse holderTechnical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (
[AFZ796015])ModelCeramic fuseSize10x38 mmVoltage typeDCRated current3 ARated voltage1,000 VUtilization categorygPV (photovoltaic protection)Rated operating frequency0 - 0 HzType of fuse status indicatorOtherRelease characteristicOtherBreaking capacity50 kAPower loss at rated current1.3 W
ETI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PV-3A10/1P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.