

## INDUSTRIAL COMPONENT DATA

# PV-400A-3L-B-15 EATON ELECTRIC FUSE 400A 1500V 3L PV BOLT-IN VER

Brand: EATON - MOELLER | Manufacturer Part Number: PV-400A-3L-B-15



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | PV-400A-3L-B-15 |
| Catalog number  | 10000           |
| Category        | HRC fuse        |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-DDDDE4A0E0   |
| Generated       | 2026-08-06      |

## Product Overview

FUSE 400A 1500V 3L PV BOLT-IN VER

Fuse-link, high speed, 400 A, DC 1500 V, 3L, 75 x 91 x 205 mm, gPV, UL, IEC, with indicator, bolted connections

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Busmann Series High speed fuses

## Additional Product Information

General specifications

Product Name Eaton Busmann series photovoltaic fuses Catalog Number PV-400A-3L-B-15 EAN 5996516001479 UPC 051712374576 Product Length/Depth 91 mm Product Height 91 mm Product Width 201.4 mm Product Weight 1614 g

Compliances CE Marked

RoHS Compliant Certifications IEC 60269

UL Listed

CSA Certified Electrical rating

Amperage Rating 400 A Interrupt rating 100 kAIC Voltage rating 1500 Vdc Watt losses 61 W Physical details

Color White Fuse type PV-3L-B-15 Material Ceramic body

ETIM for PV-400A-3L-B-15 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

3L

Type of current (EF000143)

DC

Rated voltage DC (EF012281)

1500 V

Rated current (EF000227)

400 A

Utilization category according to IEC 60269 (EF002572)

gPV (photovoltaic protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

White

Type of fuse status indicator (EF004473)

Centre fuse status indicator

Power loss at rated current (EF012389)

61 W

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

171 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PV-400A-3L-B-15 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.