

INDUSTRIAL COMPONENT DATA

PXS24-BB/80A/1m PXS24BB00001 EATON ELECTRIC Phase busbar, 1-phase, 18qmm, pin, 1m

Brand: EATON - MOELLER | Manufacturer Part Number: PXS24-BB/80A/1m



Manufacturer	EATON - MOELLER
MPN / Reference	PXS24-BB/80A/1m
Catalog number	PXS24BB00001
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-26D747B07E
Generated	2026-08-06

Product Overview

Phase busbar, 1-phase, 18qmm, pin, 1m

PXS24-BB/80A/1m

PXS24-BB/80A/1m - Busbar 1m for PXS24 Electronic overcurrent protection for 24V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Electronic overcurrent protection

Additional Product Information

Busbar 1m for PXS24 Electronic overcurrent protection for 24V DC
Reliable modular electronic overcurrent protection for 24V DC systems, simple busbar solution, fixed or variable amperages, optionally with control input and tripped message output, plug-in terminals (+ 24V and 0V) for up to 3 loads, robust design, local and (optional) remote-controllable

General specifications
Product nameEaton Moeller series xEffect - PXS24 phase busbar
Part no.PXS24-BB/80A/1m
EAN9010238036437
Product Length/Depth1000 millimetre
Product height11.5 millimetre
Product width4 millimetre
Product weight0.234 kilogram
ComplianceRoHS conform
CertificationsIEC 61373
EN45545-2
Product TradenamexEffect - PXS24
Product TypeAccessories
Product Sub TypePhase busbar
Delivery programTypeAutomation engineering
24V
Amperage rating80 A
Number of polesSingle-pole
Number of phases0
Technical Data - Electrical
Voltage rating24 V DC (15 V DC - 30 V DC)
Rated operational voltage (Ue) - max30 V
Rated surge voltage0 kV
Rated uninterrupted current (Iu)80 A
Rated conditional short-circuit current (Iq)0 kA
Rated short-time withstand current (Icw)0 kA
Electric connection typeOther
Technical Data - Mechanical
Number of modular spacings57
ColorOther
Mounting methodCan be snapped onto PXS24 modules
Cross section16 mm²
Number of channels0
Design verification as per IEC/EN 61439 - technical data
Ambient operating temperature details-30 °C - 55 °C
Permitted storage and transport temperature -

min-40 °C Permitted storage and transport temperature - max 100 °C Des...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PXS24-BB/80A/1m with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.