

INDUSTRIAL COMPONENT DATA

PXS24-IT PXS24ACC0001 EATON ELECTRIC Feed-in terminals 2,5-16qmm for PXS24-BB

Brand: EATON - MOELLER | Manufacturer Part Number: PXS24-IT



Manufacturer	EATON - MOELLER
MPN / Reference	PXS24-IT
Catalog number	PXS24ACC0001
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-9CAC96915E
Generated	2026-08-06

Product Overview

Feed-in terminals 2,5-16qmm for PXS24-BB

PXS24-IT

Eaton Moeller series xEffect - PXS24 Electronic Protection Module. Feed-in terminals 2,5-16qmm for PXS24-BB

Accessories for the 24V PXS24 fuse; supply terminal directly to the bus bar, 2.5 -16mm², max. 60A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic overcurrent protection

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - PXS24 busbar terminal Catalog Number PXS24ACC0001 Model Code PXS24-IT EAN 9010238037311 UPC 786689167677 Product Length/Depth 35 mm Product Height 12 mm Product Width 24 mm Product Weight 0.022 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Delivery program

Type Automation engineering 24V Amperage rating 60 A Technical data - electrical

Voltage rating 24 V DC (15 V DC - 30 V DC) Rated operational current 60 A Rated operational current (I_e) - max 60 A

Technical data - mechanical

Mounting method Can be snapped onto PXS24 modules Number of channels 0 Busbar thickness - min 0 mm Busbar thickness - max 0 mm Busbar width - min 0 mm Busbar width - max 0 mm Conductor cross section - max 16 mm² Width clamp 7 mm Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature details -30 °C - 55 °C Permitted storage and transport temperature - min -40 °C Permitted

storage and transport temperature - max 100 °C Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PXS24-IT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.