

INDUSTRIAL COMPONENT DATA

PXS24E-e4/F PXS24E04A002 EATON ELECTRIC Electronic overcurrent protection for 24V DC, fix 4A w/o supply term..

Brand: EATON - MOELLER | Manufacturer Part Number: PXS24E-e4/F



Manufacturer	EATON - MOELLER
MPN / Reference	PXS24E-e4/F
Catalog number	PXS24E04A002
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-E1D7307A53
Generated	2026-08-05

Product Overview

Electronic overcurrent protection for 24V DC, fix 4A w/o supply terminals

Protec. Electronic Overcurrent for 24V DC, fixed 4A without terminals

Reliable modular electronic overcurrent protection for 24V DC systems, simple busbar solution, fixed or variable amperages, optionally with control input and tripped message output, plug-in terminals (+ 24V and 0V) for up to 3 loads, robust design, local and (optional) remote-controllable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic overcurrent protection

Additional Product Information

Electronic overcurrent protection for 24V DC, fix 4A w/o supply terminals
Reliable modular electronic overcurrent protection for 24V DC systems, simple busbar solution, fixed or variable amperages, optionally with control input and tripped message output, plug-in terminals (+ 24V and 0V) for up to 3 loads, robust design, local and (optional) remote-controllable

General specifications
Product name Eaton Moeller series xEffect - PXS24 current monitoring relay

Part no. PXS24E-e4/FEAN9010238011304
Product Length/Depth 127 millimetre
Product height 93 millimetre
Product width 18 millimetre
Product weight 0.118 kilogram

Compliance CE

UL508

RoHS conform
Certifications IEC 61373

EN45545-2
Product Tradename xEffect - PXS24
Product Type Current monitoring relay
Product Sub Type None

Delivery program Type Automation engineering 24V
Technical Data - Electrical
Voltage type DC
Voltage rating 24 VDC (15 VDC - 30 VDC)
Rated control supply voltage (Us) at AC, 50 Hz - min 0 V
Rated control supply voltage (Us) at AC, 50 Hz - max 0

VRated control supply voltage (Us) at AC, 60 Hz - min0 VRated control supply voltage (Us) at AC, 60 Hz - max0 VRated control supply voltage (Us) at DC - min15 VRated control supply voltage (Us) at DC - max30 VRated operational current (Ie) fix4 ACurrent measurement - min0 ACurrent measurement - max5.2 AOverload current and short-circuit current tripType 1.3 x IN with active current limitationElectric connection typePlug-in connectionAdjustable delay-on energization time - min0 sPermitted delay-on en...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PXS24E-e4/F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.