

INDUSTRIAL COMPONENT DATA

PXS24E-e6/F PXS24E06A002 EATON ELECTRIC Electronic overcurrent protection for 24V DC, fix 6A w/o supply term..

Brand: EATON - MOELLER | Manufacturer Part Number: PXS24E-e6/F



Manufacturer	EATON - MOELLER
MPN / Reference	PXS24E-e6/F
Catalog number	PXS24E06A002
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-0E0BE2BCBD
Generated	2026-08-05

Product Overview

Electronic overcurrent protection for 24V DC, fix 6A w/o supply terminals

Protec. Electronic Overcurrent for 24V DC, fixed 6A without terminals

Reliable modular electronic overcurrent protection for 24V DC systems, simple busbar solution, fixed or variable amperages, optionally with control input and tripped message output, plug-in terminals (+ 24V and 0V) for up to 3 loads, robust design, local and (optional) remote-controllable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Electronic overcurrent protection

Additional Product Information

Electronic overcurrent protection for 24V DC, fix 6A w/o supply terminalsReliable modular electronic overcurrent protection for 24V DC systems, simple busbar solution, fixed or variable amperages, optionally with control input and tripped message output, plug-in terminals (+ 24V and 0V) for up to 3 loads, robust design, local and (optional) remote-controllable

General specificationsProduct nameEaton Moeller series xEffect - PXS24 current monitoring relayPart

no.PXS24E-e6/FEAN9010238011311Product Length/Depth127 millimetreProduct height93 millimetreProduct width18 millimetreProduct weight0.118 kilogramCompliancesUL508

CE

RoHS conformCertificationsIEC 61373

EN45545-2Product TradenamexEffect - PXS24Product TypeCurrent monitoring relayProduct Sub TypeNoneDelivery

programTypeAutomation engineering 24VTechnical Data - ElectricalVoltage typeDCVoltage rating24 VDC (15 VDC - 30 VDC)Rated control supply voltage (Us) at AC, 50 Hz - min0 VRated control supply voltage (Us) at AC, 50 Hz - max0

VRated control supply voltage (Us) at AC, 60 Hz - min0 VRated control supply voltage (Us) at AC, 60 Hz - max0 VRated control supply voltage (Us) at DC - min15 VRated control supply voltage (Us) at DC - max30 VRated operational current (Ie) fix6 ACurrent measurement - min0 ACurrent measurement - max7.8 AOverload current and short-circuit current tripType 1.3 x IN with active current limitationElectric connection typePlug-in connectionAdjustable delay-on energization time - min0 sPermitted delay-on en...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PXS24E-e6/F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.