

INDUSTRIAL COMPONENT DATA

PXS24S-e10/F/ORT PXS24S10A002 EATON ELECTRIC

Electronic overcurrent protection for 24V DC, fix 10A with trip..

Brand: EATON - MOELLER | Manufacturer Part Number: PXS24S-e10/F/ORT



Manufacturer	EATON - MOELLER
MPN / Reference	PXS24S-e10/F/ORT
Catalog number	PXS24S10A002
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-E46C62FF25
Generated	2026-08-06

Product Overview

Electronic overcurrent protection for 24V DC, fix 10A with tripped signal out-, control in-put, w/o supply terminals

Protec. Electronic overcurrent for 24V DC, fixed 10A with signal

Reliable modular electronic overcurrent protection for 24V DC systems, simple busbar solution, fixed or variable amperages, optionally with control input and tripped message output, plug-in terminals (+ 24V and 0V) for up to 3 loads, robust design, local and (optional) remote-controllable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic overcurrent protection
--------------	---

Additional Product Information

Electronic overcurrent protection for 24V DC, fix 10A with tripped signal out-, control in-put, w/o supply terminals
Reliable modular electronic overcurrent protection for 24V DC systems, simple busbar solution, fixed or variable amperages, optionally with control input and tripped message output, plug-in terminals (+ 24V and 0V) for up to 3 loads, robust design, local and (optional) remote-controllable

General specifications
Product name Eaton Moeller series xEffect - PXS24 current monitoring relay

Part no. PXS24S-e10/F/ORT
EAN 9010238011267
Product Length/Depth 127 millimetre
Product height 93 millimetre
Product width 18 millimetre
Product weight 0.118 kilogram

Compliances UL508

CE

RoHS conform
Certifications IEC 61373

EN45545-2Product TradenamexEffect - PXS24Product TypeCurrent monitoring relayProduct Sub TypeNoneDelivery programTypeAutomation engineering 24VTechnical Data - ElectricalVoltage typeDCVoltage rating24 VDC (15 VDC - 30 VDC)Rated control supply voltage (Us) at AC, 50 Hz - min0 VRated control supply voltage (Us) at AC, 50 Hz - max0 VRated control supply voltage (Us) at AC, 60 Hz - min0 VRated control supply voltage (Us) at AC, 60 Hz - max0 VRated control supply voltage (Us) at DC - min15 VRated control supply voltage (Us) at DC - max30 VRated operational current (Ie) fix10 ACurrent measurement - min0 ACurrent measurement - max13 AOverload current and short-circuit current tripType 1.3 x IN with active current limitationElectric connection typePlug-in connectionAdjustable delay-on...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PXS24S-e10/F/ORT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.