

INDUSTRIAL COMPONENT DATA

PXS24S-e2/F/ORT PXS24S02A002 EATON ELECTRIC

Electronic overcurrent protection for 24V DC, fix 2A with trippe..

Brand: EATON - MOELLER | Manufacturer Part Number: PXS24S-e2/F/ORT



Manufacturer	EATON - MOELLER
MPN / Reference	PXS24S-e2/F/ORT
Catalog number	PXS24S02A002
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-C2A70758EA
Generated	2026-08-05

Product Overview

Electronic overcurrent protection for 24V DC, fix 2A with tripped signal out-, control in-put, w/o supply terminals

Protec. Electronic overcurrent for 24V DC, fixed 2A with signal

Reliable modular electronic overcurrent protection for 24V DC systems, simple busbar solution, fixed or variable amperages, optionally with control input and tripped message output, plug-in terminals (+ 24V and 0V) for up to 3 loads, robust design, local and (optional) remote-controllable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic overcurrent protection
--------------	---

Additional Product Information

Electronic overcurrent protection for 24V DC, fix 2A with tripped signal out-, control in-put, w/o supply terminals
Reliable modular electronic overcurrent protection for 24V DC systems, simple busbar solution, fixed or variable amperages, optionally with control input and tripped message output, plug-in terminals (+ 24V and 0V) for up to 3 loads, robust design, local and (optional) remote-controllable

General specifications
Product name Eaton Moeller series xEffect - PXS24 current monitoring relay
Part

no. PXS24S-e2/F/ORT
EAN 9010238011229
Product Length/Depth 127 millimetre
Product height 93 millimetre
Product width 18 millimetre
Product weight 0.118 kilogram
Compliance CE

UL508

RoHS conform
Certifications EN45545-2

IEC 61373Product TradenamexEffect - PXS24Product TypeCurrent monitoring relayProduct Sub TypeNoneDelivery programTypeAutomation engineering 24VTechnical Data - ElectricalVoltage typeDCVoltage rating24 VDC (15 VDC - 30 VDC)Rated control supply voltage (Us) at AC, 50 Hz - min0 VRated control supply voltage (Us) at AC, 50 Hz - max0 VRated control supply voltage (Us) at AC, 60 Hz - min0 VRated control supply voltage (Us) at AC, 60 Hz - max0 VRated control supply voltage (Us) at DC - min15 VRated control supply voltage (Us) at DC - max30 VRated operational current (Ie) fix2 ACurrent measurement - min0 ACurrent measurement - max2.6 AOverload current and short-circuit current tripType 1.3 x IN with active current limitationElectric connection typePlug-in connectionAdjustable delay-on e...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PXS24S-e2/F/ORT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.