

INDUSTRIAL COMPONENT DATA

R9C3030U-DH 191859 Y7-191859 EATON ELECTRIC UL98 switch-disconnector with rotary handle

Brand: EATON - MOELLER | Manufacturer Part Number: R9C3030U-DH



Manufacturer	EATON - MOELLER
MPN / Reference	R9C3030U-DH
Catalog number	Y7-191859
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-7653500433
Generated	2026-08-05

Product Overview

UL98 switch-disconnector with rotary handle

R9C3030U-DH

Eaton Moeller® series R9 Switch-disconnector, R9, UL98, 30 A, service distribution board mounting, 3 pole, With black rotary handle

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, UL98, Part group reference: R9, With black rotary handle, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Degree of Protection: IP20, Design: service distribution board mounting, Rated uninterrupted current: $I_u = 30$ A, Standards: IEC/EN 60947, VDE 0660, CSA, UL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series R9 Switch-disconnector Catalog Number 191859 Model Code R9C3030U-DH EAN 4015081923809 Product Length/Depth 100 mm Product Height 132 mm Product Width 78 mm Product Weight 0.575 kg Certifications VDE 0660

UL

IEC/EN 60947

CSA Product specifications

Product Category Features Version as maintenance-/service switch

Version as main switch Actuator color Black 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation UV resistance only in connection with protective shield. 10.2.5 Lifting Does not apply,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / R9C3030U-DH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.