

INDUSTRIAL COMPONENT DATA

XIOC-BP-XC 260792 0004519648 EATON ELECTRIC Rack for CPUs XC100/200, expandable

Brand: EATON - MOELLER | Manufacturer Part Number: XIOC-BP-XC



Manufacturer	EATON - MOELLER
MPN / Reference	XIOC-BP-XC
Catalog number	0004519648
Category	PLC mounting rack
Minimum order	1 Pcs
Document ID	EO-6B83AE9DC7
Generated	2026-08-05

Product Overview

Rack for CPUs XC100/200, expandable

XIOC-BP-XC

Modular programmable controllers XC100 and XC200 offer an outstanding level of scalability. Different CPU performance classes and a wide range of expansion modules (XIOC-Module) are available. The compact modular PLCs XC152 facilitate cost-effective solutions of automation tasks using their computing power, the SmartWire-DT interface as well as a whole range of further interfaces. A particular feature is the ability to integrate the product into modern communication concepts. Data exchange via the Ethernet interface to OPC clients or the integrated WEB servers enables the creation of innovative solutions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > XC Modular PLC
--------------	----------------------------------

Additional Product Information

General specifications

Product Name Eaton XIOC Rack Catalog Number 260792 Model Code XIOC-BP-XC EAN 4015082607920 Product Length/Depth 107 mm Product Height 28 mm Product Width 66.5 mm Product Weight 0.095 kg Certifications CSA File No.: 012528

CSA

UL Category Control No.: NRAQ

CSA Class No.: 2252-01

CSA-C22.2 No. 142-M

UL508

UL

CE

CSA-C22.2 No. 0-M

UL File No.: E135462 General

Degree of protection IP20 Mounting method Rail mounting possible

Wall mounting/direct mounting Voltage type DC Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Communication

Number of slots 2 Input/Output

Input current at AC - max 0 A Input voltage at AC 50 Hz - min 0 V Input voltage at AC 50 Hz - max 0 V Input voltage at DC - min 0 V Input voltage at DC - max 0 V Output current at AC, 50 Hz - max 0 A Output voltage at AC 50 Hz - max 0 V Output voltage at DC - min 0 V Output voltage at DC - max 0 V Safety

Explosion safety category for dust None Explosion safety category for gas None Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XIOC-BP-XC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.