

INDUSTRIAL COMPONENT DATA

RAMO-CM1-2M0 164282 EATON ELECTRIC Motor cable, 2m, halogen free, for BOUQUET

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO-CM1-2M0



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO-CM1-2M0
Catalog number	164282
Category	Accessories/spare parts for frequency controller
Minimum order	1 Pcs
Document ID	EO-F941DAF697
Generated	2026-08-05

Product Overview

Motor cable, 2m, halogen free, for BOUQUET

Rapid Link 4.0; Motor cable; 2 m; Halogen-free; For BOUQUET

Motor cable, 2m, halogen free, for RAMO

Motor cable, halogen free, 8 x 1.5 mm², plastic plug, Length: 2 m, Terminal capacities: 8 x 1.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

Motor cable, 2m, halogen free, for RAMO
Motor cable, halogen free, 8 x 1.5 mm², plastic plug, Length: 2 m, Terminal capacities: 8 x 1.5 mm²
Delivery program

Product range
Motor feeder
Subrange
Motor cable
Basic function
for connecting the motor starter to the motor
Description
halogen free, 8 x 1.5 mm², plastic plug
For use with
For use with
RAMO
Length
2 m
Technical data
General
Standards
EN 61684

DIN VDE 0110
Degree of Protection
IP65

IEC/EN 60529
Ambient temperature
Operation [?]-30 - +70 °C
Connection cable
Terminal capacities
8 x 1.5 mm²
Outer cable diameter
9 - 13 mm
Minimum bending radius
6 x outer cable diameter mm
Material
Outer casing
halogen free

Cable: Cu flexible to VDE 0295 Class 5
Colour
Silver grey (RAL 7001)
Resistance to oils and acids
VDE 0472 Part 803

BF
Flame retardance, fire propagation
EN 50265-2-1
Metal housing with plug-in connection
Conductor cross-section
Contact pins: 8 x 1.5 mm²
Material
Contacts
Polycarbonate
Material
Contact material
Silver-plated copper
Material
Housing
Polycarbonate
Material
Locking facility
Polyamide
Design verification as per IEC/EN 61439

Operating ambient temperature min.-30 °COperating ambient temperature max.+70 °CTechnical data ETIM 7.0
Low-voltage industrial components (EG000017) / Accessories for frequency controller (EC002025)Electric engineering,
automation, process control engineering / Electrical drive / Static frequency converter / Static frequency converter
(accessory) ( [AFR303003])Type of accessoryOther
ETIM for 164282 Low-voltage industrial con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO-CM1-2M0 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.