

INDUSTRIAL COMPONENT DATA

RAMO-D00AI1S-C32RS1 150158 EATON ELECTRIC DOL starter, manual override switch, 400 V AC, 3-phase, 6.6 A, S-7..

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO-D00AI1S-C32RS1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO-D00AI1S-C32RS1
Catalog number	150158
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-F8A63F8F05
Generated	2026-08-06

Product Overview

DOL starter, manual override switch, 400 V AC, 3-phase, 6.6 A, S-7.4 for 31 modules

Rapid Link 4.0; Direct motor starter; Up to 6.6 A; 400 V; With Manual Switch

DOL starter, 6.6 A, AS-Interface®, S-7.4 for 31 modules, with manual override switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

DOL starter, 6.6 A, AS-Interface®, S-7.4 for 31 modules, with manual override switch DOL starter, Product range: motor starter, Description: Integrated thermistor monitoring PTC and thermo-click, Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation, Connections pluggable in power section, Connection of supply voltage via adapter cable on round or flexible busbar junction, Diagnostics and reset on device and via AS-Interface, with AUTO - OFF/RESET - HAND key switches, With electronic motor protection for allocated motor power from 0.09 - 3.0 kW (400 V)/0.125 - 3.0 HP (480 V), with manual override switch, Rated operational voltage: $U_e = 400$ V AC, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400$ V AC, 3-phase, Mains voltage (50/60Hz): ULN= 380 (-15%) - 480 (+10%) V, At 150% overload: $I_e = 6.6$ A, Mains voltage (50/60Hz): ULN= 380 (-15%) - 480 (+10%) V, assigned motor rating P Note: at 400 V, 50 Hz, 150 % Overload: $P = 0,09 - 3$ kW, assigned motor rating P Note: at 480 V, 60 Hz, 150 % Overload: $P = 0,125 - 3$ HP, assigned motor rating P Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, AS-Interface profile cable: S-7.4 for 31 modules, Standards: IEC/EN 60947-4-2, UL 60947-4-2, Guideline 2011/65/EU (RoHS), CE approval, UL approval, CCC approval, Degree of Protection: IP65, NEMA12 Delivery program

This item is only available until 06/30/20...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO-D00AI1S-C32RS1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.