

INDUSTRIAL COMPONENT DATA

RAMO-D04AI2S-C320S1 171778 EATON ELECTRIC DOL starter, 400 V AC, 3-phase, 6.6 A, Control voltage external br..

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO-D04AI2S-C320S1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO-D04AI2S-C320S1
Catalog number	171778
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-97D575DAA6
Generated	2026-08-05

Product Overview

DOL starter, 400 V AC, 3-phase, 6.6 A, Control voltage external brake (50/60 Hz): 400/480 V AC, S-7.A.E. for 62 modules Rapid Link 4.0; Direct motor starter; Up to 6.6 A; 400 V; External brake voltage 400 V AC

DOL starter, 6.6 A, 400/480 V AC, AS-Interface®, S-7.A.E. for 62 modules

DOL starter, Product range: motor starter, Description: Integrated thermistor monitoring PTC and thermo-click, Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation, Connections pluggable in power section, Connection of supply voltage via adapter cable on round or flexible busbar junction, Diagnostics and reset on device and via AS-Interface, with AUTO - OFF/RESET - HAND key switches, With electronic motor protection for allocated motor power from 0.09 - 3.0 kW (400 V)/0.125 - 3.0 HP (480 V), without manual override switch, Rated operational voltage: Ue= 400 V AC, 3-phase, 480 V AC, 3-phase, Output voltage with Ve: U2= 400 V AC, 3-phase, Mains voltage (50/60Hz): ULN= 380 (-15%) - 480 (+10%) V, At 150% overload: Ie= 6.6 A, Control voltage external brake (50/60 Hz): 400/480 V AC, Mains voltage (50/60Hz): ULN= 380 (-15%) - 480 (+10%) V, assigned motor rating P Note: at 400 V, 50 Hz, 150 % Overload: P= 0,09 - 3 kW, assigned motor rating P Note: at 480 V, 60 Hz, 150 % Overload: P= 0,125 - 3 HP, assigned motor rating P Note: for normal internally and external...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Rapid Link Starters

Additional Product Information

DOL starter, 6.6 A, 400/480 V AC, AS-Interface®, S-7.A.E. for 62 modules DOL starter, Product range: motor starter, Description: Integrated thermistor monitoring PTC and thermo-click, Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation, Connections pluggable in power section, Connection of supply voltage via

adapter cable on round or flexible busbar junction, Diagnostics and reset on device and via AS-Interface, with AUTO - OFF/RESET - HAND key switches, With electronic motor protection for allocated motor power from 0.09 - 3.0 kW (400 V)/0.125 - 3.0 HP (480 V), without manual override switch, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 480 (+10\%) \text{ V}$, At 150% overload: $I_e = 6.6 \text{ A}$, Control voltage external brake (50/60 Hz): 400/480 V AC, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 480 (+10\%) \text{ V}$, assigned motor rating P Note: at 400 V, 50 Hz, 150 % Overload: $P = 0,09 - 3 \text{ kW}$, assigned motor rating P Note: at 480 V, 60 Hz, 150 % Overload: $P = 0,125 - 3 \text{ HP}$, assigned motor rating P Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, AS-Interface profile cable: S-7.A.E. for 62 modules, Standards: IEC/EN 60947-4-2, UL 60947-4-2, Guideline 2011/65/EU (RoHS), CE approval, UL approval, CCC approval, Degree of Protection: IP65, NEMA12 Delivery...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO-D04AI2S-C320S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.