

INDUSTRIAL COMPONENT DATA

RAMO5-D200A31-512RS1 198518 Y7-198518 EATON ELECTRIC RAMO5-D200A31-512RS1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-D200A31-512RS1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO5-D200A31-512RS1
Catalog number	Y7-198518
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-67141DC72E
Generated	2026-08-04

Product Overview

RAMO5-D200A31-512RS1

Eaton Moeller® series Rapid Link - DOL starter, 6.6 A, Sensor input 2, AS-Interface®, S-7.4 for 31 modules, HAN Q5, with manual override switch

DOL starter, 6.6 A, Sensor input 2, AS-Interface®, S-7.4 for 31 modules, HAN Q5, with manual override switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link DOL starter Catalog Number 198518 Model Code

RAMO5-D200A31-512RS1 EAN 4015081963935 Product Length/Depth 120 mm Product Height 270 mm Product Width

220 mm Product Weight 1.8 kg Certifications UL approval

RoHS

UL 60947-4-2

CE

CCC

IEC/EN 60947-4-2 Catalog Notes Assigned motor rating: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm at 50 Hz or 1800 min at 60 Hz Features & Functions

Features Parameterization: drivesConnect mobile (App)

Diagnostics and reset on device and via AS-Interface

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: drivesConnect Fitted with: Thermistor monitoring PTC

Thermo-click

Key switch position OFF/RESET

Electronic motor protection

Manual override switch

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

Key switch position HAND

Short-circuit release

Key switch position AUTO Functions Temperature compensated overload protection

External reset possible General

Class CLASS 10 A Degree of protection NEMA 12

IP65 Electromagnetic compatibility Class A Lifespan, electrical 10,000,000 Operations (at AC-3) Lifespan, mechanical 10,000,000 Operations (at AC-3) Model Direct starter Overload release current setting - min 0.3 A Overload release current setting - max 6.6 A Overvoltage category III Product category Motor starter Protocol AS-Interface profile cable: S-7.4 for 31....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-D200A31-512RS1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.