

INDUSTRIAL COMPONENT DATA

RAMO5-D202A31-5120S1 198519 Y7-198519 EATON ELECTRIC RAMO5-D202A31-5120S1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-D202A31-5120S1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO5-D202A31-5120S1
Catalog number	Y7-198519
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-2AEE96DC4D
Generated	2026-08-04

Product Overview

RAMO5-D202A31-5120S1

Eaton Moeller® series Rapid Link - DOL starter, 6.6 A, Sensor input 2, 230/277 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q5

DOL starter, 6.6 A, Sensor input 2, 230/277 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link DOL starter Catalog Number 198519 Model Code

RAMO5-D202A31-5120S1 EAN 4015081963942 Product Length/Depth 120 mm Product Height 270 mm Product Width

220 mm Product Weight 1.63 kg Certifications UL approval

CE

CCC

RoHS

IEC/EN 60947-4-2

UL 60947-4-2 Catalog Notes Assigned motor rating: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm at 50 Hz or 1800 min at 60 Hz Features & Functions

Features Parameterization: Keypad

Diagnostics and reset on device and via AS-Interface

Parameterization: drivesConnect mobile (App)
Parameterization: Fieldbus
Parameterization: drivesConnect Fitted with: Short-circuit release
Key switch position AUTO
Key switch position OFF/RESET
Key switch position HAND
Thermistor monitoring PTC
Thermo-click
Electronic motor protection
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation Functions
Temperature compensated overload protection
External reset possible
For actuation of motors with mechanical brake General
Class CLASS 10 A Degree of protection IP65
NEMA 12 Electromagnetic compatibility Class A Lifespan, electrical 10,000,000 Operations (at AC-3) Lifespan, mechanical 10,000,000 Operations (at AC-3) Model Direct starter Overload release current setting - min 0.3 A Overload release current setting - max 6.6 A Overvoltage category III Product category Motor starter Protocol ASI
AS-Interface....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-D202A31-5120S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.