

INDUSTRIAL COMPONENT DATA

RAMO5-D204A32-4120S1 199067 Y7-199067 EATON ELECTRIC RAMO5-D204A32-4120S1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-D204A32-4120S1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO5-D204A32-4120S1
Catalog number	Y7-199067
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-DCB3EF365F
Generated	2026-08-04

Product Overview

RAMO5-D204A32-4120S1

Eaton Moeller® series Rapid Link - DOL starter, 6.6 A, Sensor input 2, 400/480 V AC, AS-Interface®, S-7.A.E. for 62 modules, HAN Q4/2

DOL starter, 6.6 A, Sensor input 2, 400/480 V AC, AS-Interface®, S-7.A.E. for 62 modules, HAN Q4/2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link DOL starter Catalog Number 199067 Model Code

RAMO5-D204A32-4120S1 EAN 4015081971251 Product Length/Depth 120 mm Product Height 270 mm Product Width 220 mm Product Weight 1.63 kg Certifications CCC

UL approval

RoHS

CE

IEC/EN 60947-4-2

UL 60947-4-2 Catalog Notes Assigned motor rating: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm at 50 Hz or 1800 min at 60 Hz Features & Functions

Features Parameterization: drivesConnect

Parameterization: Fieldbus

Parameterization: drivesConnect mobile (App)
Diagnostics and reset on device and via AS-Interface
Parameterization: Keypad Fitted with: Thermo-click
Thermistor monitoring PTC
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
Key switch position AUTO
Key switch position HAND
Electronic motor protection
Key switch position OFF/RESET
Short-circuit release Functions For actuation of motors with mechanical brake
External reset possible
Temperature compensated overload protection General
Class CLASS 10 A Degree of protection NEMA 12
IP65 Electromagnetic compatibility Class A Lifespan, electrical 10,000,000 Operations (at AC-3) Lifespan, mechanical 10,000,000 Operations (at AC-3) Model Direct starter Overload release current setting - min 0.3 A Overload release current setting - max 6.6 A Overvoltage category III Product category Motor starter Protocol AS-Interface prof...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-D204A32-4120S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.