

## INDUSTRIAL COMPONENT DATA

# RAMO5-D204A32-5120S1 198525 Y7-198525 EATON ELECTRIC RAMO5-D204A32-5120S1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-D204A32-5120S1



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | EATON - MOELLER                         |
| MPN / Reference | RAMO5-D204A32-5120S1                    |
| Catalog number  | Y7-198525                               |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-EB1B57886B                           |
| Generated       | 2026-08-03                              |

## Product Overview

RAMO5-D204A32-5120S1

DOL starter, 6.6 A, Sensor input 2, 400/480 V AC, AS-Interface®, S-7.A.E. for 62 modules, HAN Q5

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Rapid Link Starters

## Additional Product Information

DOL starter, 6.6 A, Sensor input 2, 400/480 V AC, AS-Interface®, S-7.A.E. for 62 modules, HAN Q5  
Delivery program  
Product range  
Motor starter  
Basic function  
DOL starters  
Rated operational voltage [Ue]  
400 V AC, 3-phase  
480 V AC, 3-phase  
Output voltage with  $V_e$   
[U2] = ULN  
Mains voltage (50/60Hz) [ULN]  
380 (-15%) - 480 (+10%) V  
At 150%  
overload [Ie]  
6.6 A  
Assigned motor rating  
P  
Note at 400 V, 50 Hz  
150 % Overload [P]  
0,09 - 3 kW  
Note at 480 V, 60 Hz  
150 %  
Overload [P]  
0,125 - 3 HP  
Note for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1at 50 Hz or 1800 min-1at 60 Hz  
Description  
Integrated thermistor monitoring PTC and thermo-click  
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation  
Connections pluggable in power section  
Connection of supply voltage via adapter cable on round or flexible busbar junction  
Diagnostics and reset on device and via AS-Interface  
with AUTO - OFF/RESET - HAND key switches  
With electronic motor protection for allocated motor power from 0.09 - 3.0 kW (400 V)/0.125 - 3.0 HP (480 V)  
Sensor input  
2  
Number  
Control voltage external brake (50/60 Hz)  
400/480 V AC V  
Interface/field bus (built-in)  
AS-Interface®  
AS-Interface  
profile cable  
S-7.A.E. for 62 modules  
Plug arrangement  
HAN Q5  
Parameterization  
Keypad

Fieldbus

drivesConnect

drivesConnect mobile (App)Instructionsfor actuation of motors with mechanical brakeTechnical data

GeneralStandardsIEC/EN 60947-4-2

UL 60947-4-2

Guideline 2011/65/EU (RoHS)

CE....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-D204A32-5120S1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.