

INDUSTRIAL COMPONENT DATA

RAMO5-D204A32-5120S1 198525 Y7-198525 EATON ELECTRIC RAMO5-D204A32-5120S1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-D204A32-5120S1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO5-D204A32-5120S1
Catalog number	Y7-198525
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-EB1B57886B
Generated	2026-08-05

Product Overview

RAMO5-D204A32-5120S1

DOL starter, 6.6 A, Sensor input 2, 400/480 V AC, AS-Interface®, S-7.A.E. for 62 modules, HAN Q5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Rapid Link Starters

Additional Product Information

DOL starter, 6.6 A, Sensor input 2, 400/480 V AC, AS-Interface®, S-7.A.E. for 62 modules, HAN Q5
Delivery program
Product range
Motor starter
Basic function
DOL starters
Rated operational voltage [Ue]
400 V AC, 3-phase
480 V AC, 3-phase
Output voltage with V_e
[U2] = ULN
Mains voltage (50/60Hz) [ULN]
380 (-15%) - 480 (+10%) V
At 150%
overload [Ie]
6.6 A
Assigned motor rating
P
Note at 400 V, 50 Hz
150 %
Overload [P]
0,09 - 3 kW
Note at 480 V, 60 Hz
150 %
Overload [P]
0,125 - 3 HP
Note for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1at 50 Hz or 1800 min-1at 60 Hz
Description
Integrated thermistor monitoring PTC and thermo-click
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
Connections pluggable in power section
Connection of supply voltage via adapter cable on round or flexible busbar junction
Diagnostics and reset on device and via AS-Interface
with AUTO - OFF/RESET - HAND key switches
With electronic motor protection for allocated motor power from 0.09 - 3.0 kW (400 V)/0.125 - 3.0 HP (480 V)
Sensor input
2
Number
Control voltage external brake (50/60 Hz)
400/480 V AC V
Interface/field bus (built-in)
AS-Interface®
AS-Interface
profile cable
S-7.A.E. for 62 modules
Plug arrangement
HAN Q5
Parameterization
Keypad

Fieldbus

drivesConnect

drivesConnect mobile (App)Instructionsfor actuation of motors with mechanical brakeTechnical data

GeneralStandardsIEC/EN 60947-4-2

UL 60947-4-2

Guideline 2011/65/EU (RoHS)

CE....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-D204A32-5120S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.