

INDUSTRIAL COMPONENT DATA

RAMO5-D214A31-5120S1 198528 Y7-198528 EATON

ELECTRIC RAMO5-D214A31-5120S1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-D214A31-5120S1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO5-D214A31-5120S1
Catalog number	Y7-198528
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-49612EA726
Generated	2026-08-04

Product Overview

RAMO5-D214A31-5120S1

Eaton Moeller® series Rapid Link - DOL starter, 6.6 A, Sensor input 2, Actuator output 1, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q5

DOL starter, 6.6 A, Sensor input 2, Actuator output 1, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link DOL starter Catalog Number 198528 Model Code

RAMO5-D214A31-5120S1 EAN 4015081964031 Product Length/Depth 120 mm Product Height 270 mm Product Width 220 mm Product Weight 1.64 kg Certifications UL 60947-4-2

CE

IEC/EN 60947-4-2

RoHS

UL approval

CCC Catalog Notes Assigned motor rating: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm at 50 Hz or 1800 min at 60 Hz Features & Functions

Features Parameterization: drivesConnect

Diagnostics and reset on device and via AS-Interface

Parameterization: Keypad
Parameterization: Fieldbus
Parameterization: drivesConnect mobile (App) Fitted with: Short-circuit release
Thermo-click
Key switch position HAND
Electronic motor protection
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
1 Actuator output
Key switch position AUTO
Key switch position OFF/RESET
Thermistor monitoring PTC Functions Temperature compensated overload protection
For actuation of motors with mechanical brake
External reset possible General
Class CLASS 10 A Degree of protection NEMA 12
IP65 Electromagnetic compatibility Class A Lifespan, electrical 10,000,000 Operations (at AC-3) Lifespan, mechanical 10,000,000 Operations (at AC-3) Model Direct starter Overload release current setting - min 0.3 A Overload release current setting - max 6.6 A Overvoltage category III Product category Motor starter Protocol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-D214A31-5120S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.