

INDUSTRIAL COMPONENT DATA

RAMO5-W202A32-512RS1 198534 Y7-198534 EATON ELECTRIC RAMO5-W202A32-512RS1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-W202A32-512RS1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO5-W202A32-512RS1
Catalog number	Y7-198534
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-EE7A0D8A47
Generated	2026-08-03

Product Overview

RAMO5-W202A32-512RS1

Eaton Moeller® series Rapid Link - Reversing starter, 6.6 A, Sensor input 2, 230/277 V AC, AS-Interface®, S-7.A.E. for 62 modules, HAN Q5, with manual override switch

Reversing starter, 6.6 A, Sensor input 2, 230/277 V AC, AS-Interface®, S-7.A.E. for 62 modules, HAN Q5, with manual override switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Rapid Link Starters

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Reversing starter Catalog Number 198534 Model Code

RAMO5-W202A32-512RS1 EAN 4015081964093 Product Length/Depth 120 mm Product Height 270 mm Product Width 220 mm Product Weight 1.8 kg Certifications RoHS

UL 60947-4-2

CCC

UL approval

IEC/EN 60947-4-2

CE Catalog Notes Assigned motor rating: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm at 50 Hz or 1800 min at 60 Hz Features & Functions

Features Parameterization: drivesConnect mobile (App)

Parameterization: drivesConnect

Parameterization: Fieldbus

Parameterization: Keypad

Diagnostics and reset on device and via AS-Interface Fitted with: Thermo-click

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

Manual override switch

Key switch position HAND

Key switch position AUTO

Electronic motor protection

Short-circuit release

Thermistor monitoring PTC

Key switch position OFF/RESET Functions For actuation of motors with mechanical brake

External reset possible

Temperature compensated overload protection General

Class CLASS 10 A Degree of protection IP65

NEMA 12 Electromagnetic compatibility Class A Lifespan, electrical 10,000,000 Operations (at AC-3) Lifespan, mechanical 10,000,000 Operations (at AC-3) Model Reversing starter Overload release current setting - min 0.3 A Overload release current setting - max 6.6 A Overvoltage category III Product category Motor sta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-W202A32-512RS1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.