

## INDUSTRIAL COMPONENT DATA

**RAMO5-W212A31-412RS1 199105 Y7-199105 EATON  
ELECTRIC RAMO5-W212A31-412RS1**

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-W212A31-412RS1



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | EATON - MOELLER                         |
| MPN / Reference | RAMO5-W212A31-412RS1                    |
| Catalog number  | Y7-199105                               |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-A43FD92A1E                           |
| Generated       | 2026-08-04                              |

**Product Overview**

RAMO5-W212A31-412RS1

Eaton Moeller® series Rapid Link - Reversing starter, 6.6 A, Sensor input 2, Actuator output 1, 230/277 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch

Reversing starter, 6.6 A, Sensor input 2, Actuator output 1, 230/277 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Rapid Link Starters

**Additional Product Information**

General specifications

Product Name Eaton Moeller® series Rapid Link Reversing starter Catalog Number 199105 Model Code

RAMO5-W212A31-412RS1 EAN 4015081971633 Product Length/Depth 120 mm Product Height 270 mm Product Width 220 mm Product Weight 1.81 kg Certifications UL approval

IEC/EN 60947-4-2

CCC

RoHS

UL 60947-4-2

CE Catalog Notes Assigned motor rating: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm at 50 Hz or 1800 min at 60 Hz Features & Functions

Features Parameterization: drivesConnect

Parameterization: Keypad  
Diagnostics and reset on device and via AS-Interface  
Parameterization: drivesConnect mobile (App)  
Parameterization: Fieldbus Fitted with: Key switch position AUTO  
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation  
Key switch position HAND  
Manual override switch  
Key switch position OFF/RESET  
Thermistor monitoring PTC  
1 Actuator output  
Thermo-click  
Electronic motor protection  
Short-circuit release Functions For actuation of motors with mechanical brake  
External reset possible  
Temperature compensated overload protection General  
Class CLASS 10 A Degree of protection IP65  
NEMA 12 Electromagnetic compatibility Class A Lifespan, electrical 10,000,000 Operations (at AC-3) Lifespan, mechanical 10,000,000 Operations (at AC-3) Model Reversing starter Overload release current setting - min 0.3 A Overload release current setting - max 6.6 A Overvoltage category III Product...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-W212A31-412RS1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.