

INDUSTRIAL COMPONENT DATA

RAMO5-W421PNT-4120S1 199134 Y7-199134 EATON ELECTRIC RAMO5-W421PNT-4120S1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-W421PNT-4120S1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO5-W421PNT-4120S1
Catalog number	Y7-199134
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-AEE0972D9C
Generated	2026-08-05

Product Overview

RAMO5-W421PNT-4120S1

Reversing starter, 6.6 A, Sensor input 4, Actuator output 2, 180/207 V DC, PROFINET, HAN Q4/2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Rapid Link Starters

Additional Product Information

Reversing starter, 6.6 A, Sensor input 4, Actuator output 2, 180/207 V DC, PROFINET, HAN Q4/2
Delivery program
Product range
Motor starter
Basic function
Reversing starter
Rated operational voltage [Ue]
400 V AC, 3-phase
480 V AC, 3-phase
Output voltage with Ve[U2]= ULN
Mains voltage (50/60Hz) [ULN]
380 (-15%) - 480 (+10%) V
At 150% overload [Ie]
6.6 A
Assigned motor rating P
Note at 400 V, 50 Hz
150 % Overload [P]
0,09 - 3 kW
Note at 480 V, 60 Hz
150 % Overload [P]
0,125 - 3 HP
Note for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1at 50 Hz or 1800 min-1at 60 Hz
Description
Integrated thermistor monitoring PTC and thermo-click
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
Connections pluggable in power section
Connection of supply voltage via adapter cable on round or flexible busbar junction
Diagnostics and reset on the device and via PROFINET
with AUTO - OFF/RESET - HAND key switches
With electronic motor protection for allocated motor power from 0.09 - 3.0 kW (400 V)/0.125 - 3.0 HP (480 V)
Sensor input
4
Number
Actuator output
2
Number
Control voltage external brake (50/60 Hz)
180/207 V DC V
Interface/field bus (built-in)
PROFINET
Plug arrangement
HAN Q4/2
Parameterization
Keypad

Fieldbus

drivesConnect

drivesConnect mobile (App)Instructionsfor actuation of motors with mechanical brakeTechnical data

GeneralStandardsIEC/EN 60947-4-2

UL 60947-4-2

Guideline 2011/65/EU (RoHS)

CE approval

UL approval

CCC ap...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-W421PNT-4120S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.