

INDUSTRIAL COMPONENT DATA

RAMO5-W422PNT-4120S1 199135 Y7-199135 EATON ELECTRIC RAMO5-W422PNT-4120S1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-W422PNT-4120S1



Manufacturer	EATON - MOELLER
MPN / Reference	RAMO5-W422PNT-4120S1
Catalog number	Y7-199135
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-C7EAB31DE9
Generated	2026-08-04

Product Overview

RAMO5-W422PNT-4120S1

Eaton Moeller® series Rapid Link - Reversing starter, 6.6 A, Sensor input 4, Actuator output 2, 230/277 V AC, PROFINET, HAN Q4/2

Reversing starter, 6.6 A, Sensor input 4, Actuator output 2, 230/277 V AC, PROFINET, HAN Q4/2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Reversing starter Catalog Number 199135 Model Code

RAMO5-W422PNT-4120S1 EAN 4015081971930 Product Length/Depth 120 mm Product Height 270 mm Product Width

220 mm Product Weight 1.66 kg Certifications CE

IEC/EN 60947-4-2

RoHS

CCC

UL approval

UL 60947-4-2 Catalog Notes Assigned motor rating: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm at 50 Hz or 1800 min at 60 Hz Features & Functions

Features Parameterization: Keypad

Parameterization: drivesConnect mobile (App)

Parameterization: drivesConnect

Parameterization: Fieldbus Fitted with: Thermo-click

Key switch position AUTO

Key switch position HAND

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

2 Actuator outputs

Thermistor monitoring PTC

Electronic motor protection

Key switch position OFF/RESET

Short-circuit release Functions For actuation of motors with mechanical brake

External reset possible

Temperature compensated overload protection General

Class CLASS 10 A Degree of protection NEMA 12

IP65 Electromagnetic compatibility Class A Lifespan, electrical 10,000,000 Operations (at AC-3) Lifespan, mechanical 10,000,000 Operations (at AC-3) Model Reversing starter Overload release current setting - min 0.3 A Overload release current setting - max 6.6 A Overvoltage category III Product category Motor starter Protocol PROFINET IO Rated impulse withstand voltag...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-W422PNT-4120S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.