

## INDUSTRIAL COMPONENT DATA

# RAMO5-W424EIP-412RS1 199124 Y7-199124 EATON ELECTRIC RAMO5-W424EIP-412RS1

Brand: EATON - MOELLER | Manufacturer Part Number: RAMO5-W424EIP-412RS1



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | EATON - MOELLER                         |
| MPN / Reference | RAMO5-W424EIP-412RS1                    |
| Catalog number  | Y7-199124                               |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-3DD5A98C79                           |
| Generated       | 2026-08-04                              |

## Product Overview

RAMO5-W424EIP-412RS1

Eaton Moeller® series Rapid Link - Reversing starter, 6.6 A, Sensor input 4, Actuator output 2, 400/480 V AC, Ethernet IP, HAN Q4/2, with manual override switch

Reversing starter, 6.6 A, Sensor input 4, Actuator output 2, 400/480 V AC, Ethernet IP, HAN Q4/2, with manual override switch

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Rapid Link Starters

## Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Reversing starter Catalog Number 199124 Model Code

RAMO5-W424EIP-412RS1 EAN 4015081971824 Product Length/Depth 120 mm Product Height 270 mm Product Width 220 mm Product Weight 1.83 kg Certifications CE

IEC/EN 60947-4-2

UL approval

RoHS

CCC

UL 60947-4-2 Catalog Notes Assigned motor rating: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm at 50 Hz or 1800 min at 60 Hz Features & Functions

Features Parameterization: Fieldbus

Parameterization: drivesConnect mobile (App)

Parameterization: Keypad

Parameterization: drivesConnect Fitted with: Thermistor monitoring PTC

Key switch position HAND

2 Actuator outputs

Key switch position AUTO

Manual override switch

Electronic motor protection

Thermo-click

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

Key switch position OFF/RESET

Short-circuit release Functions For actuation of motors with mechanical brake

External reset possible

Temperature compensated overload protection General

Class CLASS 10 A Degree of protection NEMA 12

IP65 Electromagnetic compatibility Class A Lifespan, electrical 10,000,000 Operations (at AC-3) Lifespan, mechanical 10,000,000 Operations (at AC-3) Model Reversing starter Overload release current setting - min 0.3 A Overload release current setting - max 6.6 A Overvoltage category III Product category Motor starter Protocol EtherNet/IP Rated i...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RAMO5-W424EIP-412RS1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.