

INDUSTRIAL COMPONENT DATA

RASP-512AI1SL-C32RS1 150215 EATON ELECTRIC Speed controller, 400 V AC, 3-phase, 5.6 A, manual override switch..

Brand: EATON - MOELLER | Manufacturer Part Number: RASP-512AI1SL-C32RS1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP-512AI1SL-C32RS1
Catalog number	150215
Category	Speed controller
Minimum order	1 Pcs
Document ID	EO-6AAED7AD0D
Generated	2026-08-03

Product Overview

Speed controller, 400 V AC, 3-phase, 5.6 A, manual override switch, Control voltage external brake (50/60 Hz): 230/277 V AC, fan, braking resistance

Rapid Link 4.0; Frequency converter; Up to 5.6 A; With manual control switch; External brake voltage 230 V AC; With braking resistance

Speed controller, 5.6 A, 2.2 kW, 230/277 V AC, AS-Interface®, S-7.4 for 31 modules, with manual override switch, with braking resistance, with fan

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Rapid Link Starters**

Additional Product Information

Speed controller, 5.6 A, 2.2 kW, 230/277 V AC, AS-Interface®, S-7.4 for 31 modules, with manual override switch, with braking resistance, with fan Speed controller, Description: integrated PTC thermistor monitoring and Thermoclick with safe isolation, Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation, optional: 4 sensor inputs with M12-Y adapter for switchover to creep speed, Connection of supply voltage via adapter cable on round or flexible busbar junction, Diagnostics and reset on device and via AS-Interface, with AUTO - OFF/RESET - HAND key switches, 3 fixed speeds and 1 potentiometer speed, can be switched over from U/f to (vector) speed control, with selector switch REV - OFF - FWD, optional: Faster stop if external 24 V fails, with manual override switch, Fan: with fan, Braking resistance: with braking resistance, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 480 (+10\%) \text{ V}$, At 150% overload: $I_e = 5.6 \text{ A}$, Control voltage external brake (50/60 Hz): 230/277 V AC, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 480 (+10\%) \text{ V}$,

assigned motor rating P Note: at 400 V, 50 Hz, 150 % Overload: P= 2.2 kW, assigned motor rating P Note: at 480 V, 60 Hz, 150 % Overload: P= 3 HP, assigned motor rating P Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP-512AI1SL-C32RS1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.