

INDUSTRIAL COMPONENT DATA

RASP5-2404A31-4120110S1 198743 Y7-198743 EATON ELECTRIC RASP5-2404A31-4120110S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-2404A31-4120110S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-2404A31-4120110S1
Catalog number	Y7-198743
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-2868DA0477
Generated	2026-08-05

Product Overview

RASP5-2404A31-4120110S1

Eaton Moeller® series Rapid Link - Speed controllers, 2.4 A, 0.75 kW, Sensor input 4, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with braking resistance, STO (Safe Torque Off)

Speed controllers, 2.4 A, 0.75 kW, Sensor input 4, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with braking resistance, STO (Safe Torque Off)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198743 Model Code

RASP5-2404A31-4120110S1 EAN 4015081968015 Product Length/Depth 157 mm Product Height 270 mm Product Width 220 mm Product Weight 3.43 kg Certifications IEC/EN 61800-5-1

UL approval

RoHS

UL 61800-5-1

CE Catalog Notes Features & Functions

Features Parameterization: Keypad

Diagnostics and reset on device and via AS-Interface

Parameterization: drivesConnect

Parameterization: Fieldbus

Parameterization: drivesConnect mobile (App) Fitted with: Selector switch (Positions: REV - OFF - FWD)

Internal DC link

Thermo-click with safe isolation

Key switch position HAND

Four fixed speeds

Control unit

PC connection

IGBT inverter

Key switch position OFF/RESET

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

Braking resistance

Key switch position AUTO

PTC thermistor monitoring

Braking resistance Functions STO (Safe Torque Off)

4-quadrant operation possible

For actuation of motors with mechanical brake

Brake chopper with braking resistance for dynamic braking General

Degree of protection IP65

NEMA 12 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III

Product category Speed controller Protocol AS-Interface profile cable: S-7.4 for 31 modules

ASI Radio interference class C1: for conducted emissions only

C2, C3: depending on the motor cable length, the connected load, and ambi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-2404A31-4120110S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.