

INDUSTRIAL COMPONENT DATA

RASP5-4400A31-412R110S1 198792 Y7-198792 EATON ELECTRIC RASP5-4400A31-412R110S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-4400A31-412R110S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-4400A31-412R110S1
Catalog number	Y7-198792
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-C4B89D20C5
Generated	2026-08-01

Product Overview

RASP5-4400A31-412R110S1

Eaton Moeller® series Rapid Link - Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch, with braking resistance, STO (Safe Torque Off)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198792 Model Code

RASP5-4400A31-412R110S1 EAN 4015081968503 Product Length/Depth 157 mm Product Height 270 mm Product Width 220 mm Product Weight 3.6 kg Certifications UL approval

RoHS

UL 61800-5-1

CE

IEC/EN 61800-5-1 Catalog Notes Features & Functions

Features Diagnostics and reset on device and via AS-Interface

Parameterization: drivesConnect mobile (App)

Parameterization: drivesConnect

Parameterization: Fieldbus

Parameterization: Keypad Fitted with: Manual override switch

Key switch position AUTO
Key switch position HAND
Braking resistance
Selector switch (Positions: REV - OFF - FWD)
Thermo-click with safe isolation
PTC thermistor monitoring
Breaking resistance
Internal DC link
PC connection
Key switch position OFF/RESET
Control unit
IGBT inverter
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation Functions 1
potentiometer speed
Brake chopper with braking resistance for dynamic braking
STO (Safe Torque Off)
3 fixed speeds
4-quadrant operation possible General
Degree of protection NEMA 12
IP65 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III Product
category Speed controller Protocol ASI
AS-Interface profile cable: S-7.4 for 31 modules Radio interference class C2, C3: depending on the motor cable length, the
connected load, and ambient conditions. External radio interference...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-4400A31-412R110S1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.