

**INDUSTRIAL COMPONENT DATA**

# RASP5-4400A31-512R100S1 198563 Y7-198563 EATON ELECTRIC RASP5-4400A31-512R100S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-4400A31-512R100S1



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | RASP5-4400A31-512R100S1            |
| Catalog number  | Y7-198563                          |
| Category        | Frequency converter less than 1 kV |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-50E93FD4D3                      |
| Generated       | 2026-08-05                         |

## Product Overview

RASP5-4400A31-512R100S1

Eaton Moeller® series Rapid Link - Speed controller, 4.3 A, 1.5 kW, Sensor input 4, AS-Interface®, S-7.4 for 31 modules, HAN Q5, with manual override switch, with braking resistance

Speed controller, 4.3 A, 1.5 kW, Sensor input 4, AS-Interface®, S-7.4 for 31 modules, HAN Q5, with manual override switch, with braking resistance

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                       |
|--------------|---------------------------------------|
| Catalog path | EATON - MOELLER > Rapid Link Starters |
|--------------|---------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198563 Model Code

RASP5-4400A31-512R100S1 EAN 4015081964383 Product Length/Depth 157 mm Product Height 270 mm Product Width 220 mm Product Weight 3.59 kg Certifications RoHS

IEC/EN 61800-5-1

CE

UL approval

UL 61800-5-1 Catalog Notes Features &amp; Functions

Features Diagnostics and reset on device and via AS-Interface

Parameterization: Keypad

Parameterization: drivesConnect mobile (App)

Parameterization: Fieldbus

Parameterization: drivesConnect Fitted with: Key switch position OFF/RESET

Key switch position HAND

Braking resistance

IGBT inverter

PTC thermistor monitoring

Thermo-click with safe isolation

PC connection

Manual override switch

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

Selector switch (Positions: REV - OFF - FWD)

Control unit

Internal DC link

Breaking resistance

Key switch position AUTO Functions 1 potentiometer speed

4-quadrant operation possible

3 fixed speeds

Brake chopper with braking resistance for dynamic braking General

Degree of protection NEMA 12

IP65 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III Product category Speed controller Protocol AS-Interface profile cable: S-7.4 for 31 modules

ASI Radio interference class C1: for conducted emissions only

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External r...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-4400A31-512R100S1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.