

INDUSTRIAL COMPONENT DATA

RASP5-4401A31-512R100S1 198763 Y7-198763 EATON ELECTRIC RASP5-4401A31-512R100S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-4401A31-512R100S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-4401A31-512R100S1
Catalog number	Y7-198763
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-BC361484D7
Generated	2026-08-04

Product Overview

RASP5-4401A31-512R100S1

Eaton Moeller® series Rapid Link - Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, 180/207 V DC, AS-Interface®, S-7.4 for 31 modules, HAN Q5, with manual override switch, with braking resistance

Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, 180/207 V DC, AS-Interface®, S-7.4 for 31 modules, HAN Q5, with manual override switch, with braking resistance

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198763 Model Code

RASP5-4401A31-512R100S1 EAN 4015081968213 Product Length/Depth 157 mm Product Height 270 mm Product Width 220 mm Product Weight 3.59 kg Certifications RoHS

CE

IEC/EN 61800-5-1

UL approval

UL 61800-5-1 Catalog Notes Features & Functions

Features Parameterization: Fieldbus

Diagnostics and reset on device and via AS-Interface

Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)
Parameterization: Keypad Fitted with: Key switch position OFF/RESET
PTC thermistor monitoring
Key switch position HAND
Breaking resistance
IGBT inverter
Manual override switch
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
Braking resistance
Thermo-click with safe isolation
PC connection
Selector switch (Positions: REV - OFF - FWD)
Internal DC link
Key switch position AUTO
Control unit Functions 3 fixed speeds
4-quadrant operation possible
Brake chopper with braking resistance for dynamic braking
1 potentiometer speed
For actuation of motors with mechanical brake General
Degree of protection IP65
NEMA 12 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III
Product category Speed controller Protocol ASI
AS-Interface profile cable: S-7.4 for 31 modules Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient condition...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-4401A31-512R100S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.