

INDUSTRIAL COMPONENT DATA

RASP5-4404A31-412R010S1 198791 Y7-198791 EATON ELECTRIC RASP5-4404A31-412R010S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-4404A31-412R010S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-4404A31-412R010S1
Catalog number	Y7-198791
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-B9850D0102
Generated	2026-08-04

Product Overview

RASP5-4404A31-412R010S1

Eaton Moeller® series Rapid Link - Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch, STO (Safe Torque Off)

Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch, STO (Safe Torque Off)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198791 Model Code

RASP5-4404A31-412R010S1 EAN 4015081968497 Product Length/Depth 157 mm Product Height 270 mm Product Width 220 mm Product Weight 3.59 kg Certifications UL approval

UL 61800-5-1

CE

IEC/EN 61800-5-1

RoHS Catalog Notes Features & Functions

Features Parameterization: drivesConnect

Parameterization: Keypad

Diagnostics and reset on device and via AS-Interface

Parameterization: drivesConnect mobile (App)
Parameterization: Fieldbus Fitted with: Manual override switch
Selector switch (Positions: REV - OFF - FWD)
Thermo-click with safe isolation
PC connection
IGBT inverter
Key switch position OFF/RESET
Key switch position HAND
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
PTC thermistor monitoring
Control unit
Internal DC link
Key switch position AUTO Functions STO (Safe Torque Off)
For actuation of motors with mechanical brake
1 potentiometer speed
3 fixed speeds General
Degree of protection IP65
NEMA 12 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III
Product category Speed controller Protocol AS-Interface profile cable: S-7.4 for 31 modules
ASI Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient conditions.
External radio interference suppression filters (optional) may be necessary.
C1: for conducted emissio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-4404A31-412R010S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.