

INDUSTRIAL COMPONENT DATA

**RASP5-4404A31-412R110S1 198795 Y7-198795 EATON
ELECTRIC RASP5-4404A31-412R110S1**

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-4404A31-412R110S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-4404A31-412R110S1
Catalog number	Y7-198795
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-43684002A5
Generated	2026-08-05

Product Overview

RASP5-4404A31-412R110S1

Eaton Moeller® series Rapid Link - Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch, with braking resistance, STO (Safe Torque Off)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Rapid Link Starters

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198795 Model Code RASP5-4404A31-412R110S1 EAN 4015081968534 Product Length/Depth 157 mm Product Height 270 mm Product Width 220 mm Product Weight 3.6 kg Certifications UL approval

UL 61800-5-1

CE

IEC/EN 61800-5-1

RoHS Catalog Notes Features & Functions

Features Parameterization: Keypad

Parameterization: Fieldbus

Diagnostics and reset on device and via AS-Interface

Parameterization: drivesConnect mobile (App)

Parameterization: drivesConnect Fitted with: Manual override switch

Internal DC link
Key switch position AUTO
Braking resistance
PC connection
IGBT inverter
Key switch position OFF/RESET
Key switch position HAND
Selector switch (Positions: REV - OFF - FWD)
Control unit
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
PTC thermistor monitoring
Thermo-click with safe isolation
Braking resistance Functions STO (Safe Torque Off)
1 potentiometer speed
4-quadrant operation possible
3 fixed speeds
Brake chopper with braking resistance for dynamic braking
For actuation of motors with mechanical brake General
Degree of protection NEMA 12
IP65 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III Product category Speed controller Protocol ASI
AS-Interface profile cable: S-7.4 for 31 modules Radio interference class C2, C3: depending on the motor cable length, the connected load,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-4404A31-412R110S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.