

INDUSTRIAL COMPONENT DATA

RASP5-4420PNT-4120010S1 198972 Y7-198972 EATON ELECTRIC RASP5-4420PNT-4120010S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-4420PNT-4120010S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-4420PNT-4120010S1
Catalog number	Y7-198972
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-C62F8F695F
Generated	2026-08-03

Product Overview

RASP5-4420PNT-4120010S1

Eaton Moeller® series Rapid Link - Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, Actuator output 2, PROFINET, HAN Q4/2, STO (Safe Torque Off)

Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, Actuator output 2, PROFINET, HAN Q4/2, STO (Safe Torque Off)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198972 Model Code

RASP5-4420PNT-4120010S1 EAN 4015081970308 Product Length/Depth 157 mm Product Height 270 mm Product Width

220 mm Product Weight 3.45 kg Certifications RoHS

UL 61800-5-1

CE

UL approval

IEC/EN 61800-5-1 Catalog Notes Features & Functions

Features Parameterization: drivesConnect mobile (App)

Parameterization: drivesConnect

Parameterization: Keypad

Parameterization: Fieldbus Fitted with: Key switch position OFF/RESET

Key switch position HAND
IGBT inverter
PC connection
Key switch position AUTO
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
PTC thermistor monitoring
Thermo-click with safe isolation
Selector switch (Positions: REV - OFF - FWD)
2 Actuator outputs
Control unit
Internal DC link Functions 3 fixed speeds
STO (Safe Torque Off)
1 potentiometer speed General
Degree of protection IP65
NEMA 12 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III
Product category Speed controller Protocol PROFINET IO Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
C1: for conducted emissions only Rated impulse withstand voltage (Uimp) 2000 V System configuration type AC voltage Center-point earthed star network (TN-S network)
Phas...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-4420PNT-4120010S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.