

INDUSTRIAL COMPONENT DATA

**RASP5-4421EIP-412R010S1 198893 Y7-198893 EATON
ELECTRIC RASP5-4421EIP-412R010S1**

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-4421EIP-412R010S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-4421EIP-412R010S1
Catalog number	Y7-198893
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-6128EBBEF4
Generated	2026-08-05

Product Overview

RASP5-4421EIP-412R010S1

Eaton Moeller® series Rapid Link - Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, Actuator output 2, 180/207 V DC, Ethernet IP, HAN Q4/2, with manual override switch, STO (Safe Torque Off)

Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, Actuator output 2, 180/207 V DC, Ethernet IP, HAN Q4/2, with manual override switch, STO (Safe Torque Off)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Rapid Link Starters

Additional Product Information

General specifications

Product Name Eaton Rapid Link Speed controller

Catalog Number 198893

Model Code RASP5-4421EIP-412R010S1

EAN 4015081969517

Product Length/Depth 157 mm

Product Height 270 mm

Product Width 220 mm

Product Weight 3.6 kg

Certifications CE

IEC/EN 61800-5-1

RoHS

UL 61800-5-1

UL approval

Catalog Notes 3 fixed speeds and 1 potentiometer speed

can be switched over from U/f to (vector) speed control

Connection of supply voltage via adapter cable on round or flexible busbar junction

Diagnostics and reset on the device and via Ethernet IP

integrated PTC thermistor monitoring and Thermoclick with safe isolation

optional: 4 sensor inputs with M12-Y adapter for switchover to creep speed

optional: Faster stop if external 24 V fails

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

with AUTO - OFF/RESET - HAND key switches

with selector switch REV - OFF - FWD

Features & Functions

Features Parameterization: Keypad

Parameterization: Fieldbus

Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Fitted with: Key switch position AUTO

2 Actuator outputs

Manual override switch

Selector switch (Positions: REV - OFF - FWD)

Control unit

PTC thermistor monitoring

Internal DC link

PC connection

IGBT inverter

Key switch position OFF/RESET

Key switch position HAND

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

Thermo-click with safe isolation

Functions 1 poten...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-4421EIP-412R010S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.