

INDUSTRIAL COMPONENT DATA

RASP5-4422PNT-4120100S1 198970 Y7-198970 EATON ELECTRIC RASP5-4422PNT-4120100S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-4422PNT-4120100S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-4422PNT-4120100S1
Catalog number	Y7-198970
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-8CDBFE225F
Generated	2026-08-04

Product Overview

RASP5-4422PNT-4120100S1

Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, Actuator output 2, 230/277 V AC, PROFINET, HAN Q4/2, with braking resistance

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Rapid Link Starters

Additional Product Information

Speed controllers, 4.3 A, 1.5 kW, Sensor input 4, Actuator output 2, 230/277 V AC, PROFINET, HAN Q4/2, with braking resistance
Delivery program

Product rangeSpeed controllerRated operational voltage [Ue]400 V AC, 3-phase

480 V AC, 3-phaseOutput voltage with Ve[U2]0 - ULNMains voltage (50/60Hz) [ULN]380 (-15%) - 480 (+10%) VAt 150%

overload [Ie]4.3 Aassigned motor rating PNoteat 400 V, 50 Hz150 % Overload [P]1.5 kWNoteat 480 V, 60 Hz150 %

Overload [P]2 HPNotefor normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1at 50 Hz or 1800 min-1at 60 HzDescriptionintegrated PTC thermistor monitoring and Thermoclick with safe isolation

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

optional: 4 sensor inputs with M12-Y adapter for switchover to creep speed

Connection of supply voltage via adapter cable on round or flexible busbar junction

Diagnostics and reset on the device and via PROFINET

with AUTO - OFF/RESET - HAND key switches

3 fixed speeds and 1 potentiometer speed

can be switched over from U/f to (vector) speed control

with selector switch REV - OFF - FWD

optional: Faster stop if external 24 V fails
Sensor input 4 Number
Actuator output 2 Number
Control voltage external brake
(50/60 Hz) 230/277 V AC V
Interface/field bus (built-in) PROFINET
Plug arrangement HAN Q4/2
Braking resistance with braking
resistance
Parameterization Keypad

Fieldbus

drivesConnect

drivesConnect mobile (App) Instructions for....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-4422PNT-4120100S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.