

INDUSTRIAL COMPONENT DATA

RASP5-5400A31-412R000S1 198816 Y7-198816 EATON ELECTRIC RASP5-5400A31-412R000S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-5400A31-412R000S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-5400A31-412R000S1
Catalog number	Y7-198816
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-C842C77F0A
Generated	2026-08-06

Product Overview

RASP5-5400A31-412R000S1

Eaton Moeller® series Rapid Link - Speed controllers, 5.6 A, 2.2 kW, Sensor input 4, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch

Speed controllers, 5.6 A, 2.2 kW, Sensor input 4, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198816 Model Code

RASP5-5400A31-412R000S1 EAN 4015081968749 Product Length/Depth 157 mm Product Height 270 mm Product Width 220 mm Product Weight 3.58 kg Certifications CE

UL approval

IEC/EN 61800-5-1

RoHS

UL 61800-5-1 Catalog Notes Features & Functions

Features Diagnostics and reset on device and via AS-Interface

Parameterization: Keypad

Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Parameterization: Fieldbus Fitted with: Key switch position AUTO

Control unit

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

Internal DC link

Key switch position HAND

Manual override switch

PTC thermistor monitoring

PC connection

Key switch position OFF/RESET

Thermo-click with safe isolation

IGBT inverter

Selector switch (Positions: REV - OFF - FWD) Functions 3 fixed speeds

1 potentiometer speed General

Degree of protection IP65

NEMA 12 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III

Product category Speed controller Protocol ASI

AS-Interface profile cable: S-7.4 for 31 modules Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

C1: for conducted emissions only Rated impulse withstand voltage (Uimp) 2000 V System configu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-5400A31-412R000S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.