

INDUSTRIAL COMPONENT DATA

RASP5-5404A31-4120000S1 198803 Y7-198803 EATON ELECTRIC RASP5-5404A31-4120000S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-5404A31-4120000S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-5404A31-4120000S1
Catalog number	Y7-198803
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-6DEE2D51BF
Generated	2026-08-05

Product Overview

RASP5-5404A31-4120000S1

Eaton Moeller® series Rapid Link - Speed controllers, 5.6 A, 2.2 kW, Sensor input 4, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2

Speed controllers, 5.6 A, 2.2 kW, Sensor input 4, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198803 Model Code

RASP5-5404A31-4120000S1 EAN 4015081968619 Product Length/Depth 157 mm Product Height 270 mm Product Width

220 mm Product Weight 3.41 kg Certifications UL approval

IEC/EN 61800-5-1

UL 61800-5-1

RoHS

CE Catalog Notes Features & Functions

Features Parameterization: Fieldbus

Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Diagnostics and reset on device and via AS-Interface

Parameterization: Keypad Fitted with: PC connection

Key switch position HAND

Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

Selector switch (Positions: REV - OFF - FWD)

IGBT inverter

Key switch position AUTO

Control unit

Key switch position OFF/RESET

PTC thermistor monitoring

Four fixed speeds

Thermo-click with safe isolation

Internal DC link Functions For actuation of motors with mechanical brake General

Degree of protection NEMA 12

IP65 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III Product category Speed controller Protocol AS-Interface profile cable: S-7.4 for 31 modules

ASI Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient conditions.

External radio interference suppression filters (optional) may be necessary.

C1: for conducted emissions only Rated impulse withstand voltage (Uimp) 2000 V System con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-5404A31-4120000S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.