

INDUSTRIAL COMPONENT DATA

RASP5-5424PNT-412R010S1 199023 Y7-199023 EATON ELECTRIC RASP5-5424PNT-412R010S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-5424PNT-412R010S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-5424PNT-412R010S1
Catalog number	Y7-199023
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-13F5F59948
Generated	2026-08-04

Product Overview

RASP5-5424PNT-412R010S1

Eaton Moeller® series Rapid Link - Speed controllers, 5.6 A, 2.2 kW, Sensor input 4, Actuator output 2, 400/480 V AC, PROFINET, HAN Q4/2, with manual override switch, STO (Safe Torque Off)

Speed controllers, 5.6 A, 2.2 kW, Sensor input 4, Actuator output 2, 400/480 V AC, PROFINET, HAN Q4/2, with manual override switch, STO (Safe Torque Off)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Rapid Link Starters**

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 199023 Model Code

RASP5-5424PNT-412R010S1 EAN 4015081970810 Product Length/Depth 157 mm Product Height 270 mm Product Width 220 mm Product Weight 3.62 kg Certifications UL 61800-5-1

UL approval

CE

IEC/EN 61800-5-1

RoHS Catalog Notes Features & Functions

Features Parameterization: drivesConnect mobile (App)

Parameterization: Keypad

Parameterization: Fieldbus

Parameterization: drivesConnect Fitted with: 2 Actuator outputs
PTC thermistor monitoring
Thermo-click with safe isolation
PC connection
Key switch position HAND
Key switch position AUTO
Key switch position OFF/RESET
Selector switch (Positions: REV - OFF - FWD)
Control unit
Manual override switch
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
Internal DC link
IGBT inverter Functions 3 fixed speeds
STO (Safe Torque Off)
1 potentiometer speed
For actuation of motors with mechanical brake General
Degree of protection NEMA 12
IP65 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III Product category Speed controller Protocol PROFINET IO Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary. C1: for conducted emissions only Rated impulse withstand voltage (Uimp) 2000 V System configuration....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-5424PNT-412R010S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.