

INDUSTRIAL COMPONENT DATA

RASP5-8400A31-412R101S1 198856 Y7-198856 EATON ELECTRIC RASP5-8400A31-412R101S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-8400A31-412R101S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-8400A31-412R101S1
Catalog number	Y7-198856
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-4363971A20
Generated	2026-08-03

Product Overview

RASP5-8400A31-412R101S1

Eaton Moeller® series Rapid Link - Speed controllers, 8.5 A, 4 kW, Sensor input 4, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch, with braking resistance, with fan

Speed controllers, 8.5 A, 4 kW, Sensor input 4, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with manual override switch, with braking resistance, with fan

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Rapid Link Starters**

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198856 Model Code

RASP5-8400A31-412R101S1 EAN 4015081969142 Product Length/Depth 195 mm Product Height 270 mm Product Width 220 mm Product Weight 3.78 kg Certifications UL 61800-5-1

CE

RoHS

UL approval

IEC/EN 61800-5-1 Catalog Notes Features & Functions

Features Internal and on heat sink, temperature-controlled Fan

Parameterization: Fieldbus

Diagnostics and reset on device and via AS-Interface

Parameterization: drivesConnect mobile (App)
Parameterization: drivesConnect
Parameterization: Keypad Fitted with: Braking resistance
Thermo-click with safe isolation
Fan
Key switch position AUTO
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
Selector switch (Positions: REV - OFF - FWD)
PTC thermistor monitoring
Control unit
PC connection
IGBT inverter
Manual override switch
Key switch position HAND
Internal DC link
Braking resistance
Key switch position OFF/RESET Functions Brake chopper with braking resistance for dynamic braking
3 fixed speeds
4-quadrant operation possible
1 potentiometer speed General
Degree of protection NEMA 12
IP65 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III Product category Speed controller Protocol AS-Interface profile cable: S-7.4 for 31 modules
ASI Radio interference class C1: for conducted emissions only
C2, C3: depending on the motor cable leng...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-8400A31-412R101S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.