

INDUSTRIAL COMPONENT DATA

RASP5-8402A31-5120101S1 198582 Y7-198582 EATON ELECTRIC RASP5-8402A31-5120101S1

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-8402A31-5120101S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-8402A31-5120101S1
Catalog number	Y7-198582
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-7A0A9CD604
Generated	2026-08-06

Product Overview

RASP5-8402A31-5120101S1

Eaton Moeller® series Rapid Link - Speed controller, 8.5 A, 4 kW, Sensor input 4, 230/277 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q5, with braking resistance, with fan

Speed controller, 8.5 A, 4 kW, Sensor input 4, 230/277 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q5, with braking resistance, with fan

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Rapid Link Starters
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198582 Model Code

RASP5-8402A31-5120101S1 EAN 4015081964574 Product Length/Depth 195 mm Product Height 270 mm Product Width 220 mm Product Weight 3.61 kg Certifications IEC/EN 61800-5-1

CE

UL 61800-5-1

RoHS

UL approval Catalog Notes Features & Functions

Features Diagnostics and reset on device and via AS-Interface

Internal, temperature-controlled Fan

Parameterization: drivesConnect

Parameterization: Keypad
Parameterization: Fieldbus
Parameterization: drivesConnect mobile (App) Fitted with: Fan
Internal DC link
Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation
PTC thermistor monitoring
PC connection
Selector switch (Positions: REV - OFF - FWD)
Key switch position AUTO
Key switch position HAND
Braking resistance
Control unit
Breaking resistance
Key switch position OFF/RESET
IGBT inverter
Thermo-click with safe isolation Functions For actuation of motors with mechanical brake
3 fixed speeds
1 potentiometer speed
4-quadrant operation possible
Brake chopper with braking resistance for dynamic braking General
Degree of protection IP65
NEMA 12 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III
Product category Speed controller Protocol AS-Interface profile cable: S-7.4 for 31 modules
ASI Radio interference class C1: for conducted emissions only
C2, C3: depending on the motor cabl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-8402A31-5120101S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.