

INDUSTRIAL COMPONENT DATA

**RASP5-8404A31-4120111S1 198851 Y7-198851 EATON
ELECTRIC RASP5-8404A31-4120111S1**

Brand: EATON - MOELLER | Manufacturer Part Number: RASP5-8404A31-4120111S1



Manufacturer	EATON - MOELLER
MPN / Reference	RASP5-8404A31-4120111S1
Catalog number	Y7-198851
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-4B8454004D
Generated	2026-08-06

Product Overview

RASP5-8404A31-4120111S1

Eaton Moeller® series Rapid Link - Speed controllers, 8.5 A, 4 kW, Sensor input 4, 400/480 V AC, AS-Interface®, S-7.4 for 31 modules, HAN Q4/2, with braking resistance, STO (Safe Torque Off), with fan

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Rapid Link Starters

Additional Product Information

General specifications

Product Name Eaton Moeller® series Rapid Link Speed controller Catalog Number 198851 Model Code RASP5-8404A31-4120111S1 EAN 4015081969098 Product Length/Depth 195 mm Product Height 270 mm Product Width 220 mm Product Weight 3.62 kg Certifications UL 61800-5-1

UL approval

CE

IEC/EN 61800-5-1

RoHS Catalog Notes Features & Functions

Features Parameterization: drivesConnect mobile (App)

Internal and on heat sink, temperature-controlled Fan

Parameterization: Keypad

Diagnostics and reset on device and via AS-Interface

Parameterization: drivesConnect

Parameterization: Fieldbus Fitted with: Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation

Internal DC link

Breaking resistance

Selector switch (Positions: REV - OFF - FWD)

Braking resistance

Thermo-click with safe isolation

Key switch position OFF/RESET

PTC thermistor monitoring

Control unit

PC connection

IGBT inverter

Key switch position HAND

Fan

Key switch position AUTO Functions For actuation of motors with mechanical brake

Brake chopper with braking resistance for dynamic braking

4-quadrant operation possible

1 potentiometer speed

STO (Safe Torque Off)

3 fixed speeds General

Degree of protection NEMA 12

IP65 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Overvoltage category III Product category Speed controller Protocol ASI

AS-Interface profile cable: S-7.4 for 31 modules Radio interference class C2, C3: depending on the moto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RASP5-8404A31-4120111S1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.