


INDUSTRIAL COMPONENT DATA

+IZMX-RP16-1250 124157 EATON ELECTRIC Rating plug, 1250A, IZMX16

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-RP16-1250



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-RP16-1250
Catalog number	124157
Category	Current transformer
Minimum order	1 Pcs
Document ID	EO-92C86C0757
Generated	2026-08-06

Product Overview

Rating plug, 1250A, IZMX16

Rate current module for adapting to changes in the basic conditions for an application. The rate current module's nominal value must be less than or equal to the basic device's rated current. The rate current module can be replaced on site without replacing the transformer. Rate current module 200 A, 250 A and 300 A can be combined with P-trip units.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Rating plug, 1250A, IZMX16 Rate current module for adapting to changes in the basic conditions for an application. The rate current module's nominal value must be less than or equal to the basic device's rated current. The rate current module can be replaced on site without replacing the transformer. Rate current module 200 A, 250 A and 300 A can be combined with P-trip units. [Delivery program

Product range Accessories Accessories Options / accessories trip blocks Accessories Rating Plug (rate current module)

The rated current can be reduced by changing the rating plug, for example, in order to adapt to changed conditions in the application.

The rating plug's nominal value must be less than or equal to the basic device's rated current.

The rating plug can be replaced on site without replacing the transformer.

200 A, 250 A and 300 A rating plugs cannot be combined with P-trip units. Rated current [In] 1250 A Suitable for circuit-breaker Iu= Iu= 1600 A For use with IZMX16 , Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C , Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Current transformer (EC002048) Electric engineering, automation, process control engineering / Signal processing / Transformer / Current transformer ( [AAB626014]) Model Through-feed current converter Primary rated current 1250 A Secondary rated current 0 A Secondary rated apparent power 0 VA Ac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-RP16-1250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.